















Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
SWITCH				
MO120006		<p><u>FS105D 5 portova ethernet switch</u></p> <ul style="list-style-type: none"> - Portova 5X RJ-45 10/100 Mbps - Switching Capacity 1 Gbps - Packet Forwarding Rate 0.744 Mpps - MAC Table Size 1K - Radna temperatura 0 °C do +45 °C - Sa AC/DC adapterom 5 V DC 0,55 A - Dimenzije 88,2 × 52,7 × 21,8 mm 		
MO120007		<p><u>FS108D 8 portova ethernet switch</u></p> <ul style="list-style-type: none"> - Portova 8X RJ-45 10/100 Mbps - Switching Capacity 1,6 Gbps - Packet Forwarding Rate 1,1904 Mpps - Packet Buffer Size 570 kbit - MAC Table Size 2K - Radna temperatura 0 °C do +40 °C - Sa AC/DC adapterom 5 V DC, 0,55 A - Dimenzije 138 × 61,5 × 24 mm 		
MO120004		<p><u>GS105D 5 portova ethernet switch</u></p> <ul style="list-style-type: none"> - Portova 5X RJ-45 10/100/1000 Mbps - Switching Capacity 10 Gbps - Packet Forwarding Rate 7,44 Mpps - MAC Table Size 2K - Packet Buffer Size 1 Mbit - IGMP Snooping - Radna temperatura 0 °C do +40 °C - Sa AC/DC adapterom 5 V DC 0,55 A - Dimenzije 88 × 52,5 × 24 mm 		
MO120005		<p><u>GS108D 8 portova ethernet switch</u></p> <ul style="list-style-type: none"> - Portova 8X RJ-45 10/100/1000 Mbps - Switching Capacity 16 Gbps - Packet Forwarding Rate 11,904 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - IGMP Snooping, Loop Prevention, Loop Detection - Radna temperatura 0 °C do +40 °C - Sa AC/DC adapterom 5 V DC, 0,55 A - Dimenzije 138 × 61,5 × 24 mm 		

MO120008		<p><u>GS1016 16 portova ethernet switch</u></p> <ul style="list-style-type: none"> - Portova 16X RJ-45 10/100/1000 Mbps - Switching Capacity 32 Gbps - Packet Forwarding Rate 23,808 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - DIP prekidac: Default/VLAN (1-14)/Extend (1-14 250m 10Mbps) - L2: IGMP Snooping, Loop Prevention, Loop Detection, DSCP QoS, 802.1p QoS - Radna temperatura 0 °C do +40 °C - Napajanje AC 90-260V~ 50/60Hz - Dimenzije 200 × 118 × 44 mm - Nosaci za montazu u rack 		
MO120009		<p><u>GS1024 24 portova ethernet switch</u></p> <ul style="list-style-type: none"> - Portova 24X RJ-45 10/100/1000 Mbps - Switching Capacity 48 Gbps - Packet Forwarding Rate 35,712 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - DIP prekidac: Default/VLAN (1-22)/Extend (1-22 250m 10Mbps) - L2: IGMP Snooping, Loop Prevention, Loop Detection, DSCP QoS, 802.1p QoS - Radna temperatura 0 °C do +40 °C - Napajanje AC 90-260V~ 50/60Hz - Dimenzije 270 × 182 × 44 mm - Nosaci za montazu u rack 		
POE SWITCH				
MO120001		<p><u>FS1006P 4 PoE +2 portova ethernet switch 65W</u></p> <ul style="list-style-type: none"> - Portovi: 4X RJ-45 10/100 Mbps (PoE+), uplink 2X RJ-45 10/100 Mbps - Switching Capacity 1,2 Gbps - Packet Forwarding Rate 0,8928 Mpps - Packet Buffer Size 0,768 Mbit - MAC Table Size 2K - DIP prekidac: Default/VLAN (1-4)/Extend (1-4 250m 10Mbps) - PoE Watchdog restartuje povezane uređaje koji su neaktivni duže od 5 minuta. - PoE standard: IEEE802.3af; IEEE802.3at - Maksimalna PoE snaga porta 30W - Radna temperatura 0 °C do +40 °C - Napajanje AC 90-260V~ 50/60Hz - Dimenzije 200 × 118 × 44 mm 		

MO120002		<p><u>FS1010PG 8 PoE +2 portova ethernet switch 120W</u></p> <ul style="list-style-type: none"> - Portovi: 8X RJ-45 10/100 Mbps (PoE+), uplink 2X RJ-45 10/100/1000 Mbps - Switching Capacity 5,6 Gbps - Packet Forwarding Rate 4,166 Mpps - Packet Buffer Size 2 Mbit - MAC Table Size 2K - DIP prekidac: PoE Watchdog/VLAN (1-8)/Extend (1-8 250m 10Mbps) - PoE Watchdog restartuje povezane uređaje koji su neaktivni duže od 5 minuta - Inteligentno upravljanje napajanjem: automatski isključuje poslednji priključeni uređaj kada potrošnja energije premaši raspoloživi budžet napajanja - PoE standard: IEEE802.3af; IEEE802.3at - Maksimalna PoE snaga porta 30W - Radna temperatura 0 °C do +40 °C - Napajanje AC 100-240V~ 50/60Hz - Dimenzije 200 × 118 × 44 mm 		
MO120003		<p><u>GS1010PE 8 PoE +2 portova ethernet switch 120W</u></p> <ul style="list-style-type: none"> - Portovi: 8X RJ-45 10/100/1000 Mbps (PoE+), uplink 2X RJ-45 10/100/1000 Mbps - Switching Capacity 20 Gbps - Packet Forwarding Rate 14,88 Mpps - Packet Buffer Size 1 Mbit - MAC Table Size 2K - DIP prekidac: PoE Watchdog/VLAN (1-8)/Extend (1-8 250m 10Mbps) - PoE Watchdog restartuje povezane uređaje koji su neaktivni duže od 5 minuta - Inteligentno upravljanje napajanjem: automatski isključuje poslednji priključeni uređaj kada potrošnja energije premaši raspoloživi budžet napajanja - PoE standard: IEEE802.3af; IEEE802.3at - Maksimalna PoE snaga porta 30W - Radna temperatura 0 °C do +40 °C - Napajanje AC 100-240V~ 50/60Hz - Dimenzije 256 × 170 × 44 mm 		

MO1200010		<p><u>FS1026PS1 24 PoE + 2 RJ45 + 1 SFTP port ethernet switch 300 W</u></p> <ul style="list-style-type: none"> - Portovi: 24X RJ-45 10/100 Mbps (PoE+), uplink 2X RJ-45 10/100/1000 Mbps , uplink 1X SFTP 1,25 G - Switching Capacity 10,8 Gbps - Packet Forwarding Rate 14,88 Mpps - Packet Buffer Size 2 Mbit - MAC Table Size 2K - DIP prekidač: PoE Watchdog/VLAN (1-24)/ Extend (17-24 250m 10Mbps) - PoE Watchdog restartuje povezane uređaje koji su neaktivni duže od 5 minuta - Inteligentno upravljanje napajanjem: automatski isključuje poslednji priključeni uređaj kada potrošnja energije premaši raspoloživi budžet napajanja - PoE standard: IEEE802.3af; IEEE802.3at - Maksimalna PoE snaga porta 30W - Radna temperatura 0 °C do +40 °C - Napajanje AC 100-240V~ 50/60Hz - Dimenzije 440 × 180 × 44 mm - Nosaci za montazu u rack 		
Wi-Fi ROUTER				
MO120108		<p><u>WR3000 AX3000 Wi-Fi 6 router</u></p> <ul style="list-style-type: none"> - Wi-Fi 6, 5 GHz do 2402 Mbps, 2,4 GHz do 574 Mbps - Portovi: WAN 1X RJ-45 10/100/1000 Mbps, LAN 3X RJ-45 10/100/1000 Mbps - Beamforming - Antene 4 spoljasnje - Maksimalni broj klijenata 128, preporuceno do 70 - Režimi rada: Wi-Fi Router, Access Point, Range Extender, WISP, Client - Cudy Mesh, Mesh međuveza: Wireless, Wired, višepojasna međuveza - WAN režimi: DHCP, Static IP, PPPOE, PPTP, L2TP - QoS, IPv4/IPv6, Multicast, IPTV/VLAN, TTL Customization, IGMP, Forwarding, Firewall - VPN Server i Client - Radna temperatura 0 °C do 40 °C - Sa AC/DC adapterom 12 V, 1 A - Dimenzije 183 × 109 × 35 mm 		

MO120109		<p><u>WR1500 AX1500 Wi-Fi 6 router</u></p> <ul style="list-style-type: none"> - Wi-Fi 6, 5 GHz do 1201 Mbps, 2,4 GHz do 300 Mbps - Portovi: WAN 1X RJ-45 10/100/1000 Mbps, LAN 3X RJ-45 10/100/1000 Mbps - Beamforming - Antene 4 spoljasnje - Maksimalni broj klijenata 128, preporuceno do 60 - Reжими rada: Wi-Fi Router, Access Point, Range Extender, WISP, Client - Cudy Mesh, Mesh međuveza: Wireless, Wired, višepojasna međuveza - WAN reжими: DHCP, Static IP, PPPOE, PPTP, L2TP - QoS, IPv4/IPv6, Multicast, IPTV/VLAN, IGMP, Forwarding, Firewall - VPN Client - Radna temperatura 0 °C do 40 °C - Sa AC/DC adapterom 12 V, 1 A - Dimenzije 183 × 109 × 35 mm 		
MO120107		<p><u>WR300 N300 Wi-Fi 2,4 GHz router</u></p> <ul style="list-style-type: none"> - Wi-Fi 2,4 GHz do 300 Mbps - Portovi: WAN 1X RJ-45 10/100 Mbps, LAN 3X RJ-45 10/100 Mbps - Antene 2 spoljasnje - Maksimalni broj klijenata 64, preporuceno do 30 - Reжими rada: Wi-Fi Router, Access Point, Range Extender, WISP, Client - Cudy Mesh, Mesh međuveza: Wireless, Wired - WAN reжими: DHCP, Static IP, PPPOE, PPTP, L2TP - QoS, IPv4/IPv6, Multicast, IPTV/VLAN, TTL Customization, IGMP, Forwarding, Firewall - VPN Client - Radna temperatura 0 °C do 40 °C - Sa AC/DC adapterom 5 V, 1 A - Dimenzije 118 × 80 × 28 mm 		

<p>MO120110</p>		<p>LT400 4G N300 Wi-Fi 4 Router</p> <ul style="list-style-type: none"> - 4G Cat. 4, DL do 150 Mbps, UL do 50 Mbps - Wi-Fi 2,4 GHz do 300 Mbps - 1x Nano SIM Slot - Portovi: WAN/LAN 1X RJ-45 10/100 Mbps, LAN 3X RJ-45 10/100 Mbps - Antene: LTE 2 spoljasnje, Wi-Fi 2 spoljasnje - Maksimalni broj klijenata 64, preporuceno do 30 - Reziimi rada: Cellular Router, Wi-Fi Router, WISP - Cellular Mode: 4G Only, Auto - WAN reziimi: DHCP, Static IP, PPPOE - Sekvenca prebacivanja u slučajju pada interneta: WAN, WISP, Cellular - QoS, IPv4/IPv6, Multicast, IPTV/VLAN, TTL Customization, IGMP, Forwarding, Firewall - VPN Server i Client - Radna temperatura 0 °C do 40 °C - Sa AC/DC adapterom 12 V, 1 A - Dimenzije 229 x 123 x 33 mm 		
-----------------	---	--	--	--

ACCESS POINT


MO120102





AP1300 AC1200 Wi-Fi 5 2,4 i 5 GHz

Access Point

- Wi-Fi 2,4 GHz do 300 Mbps, 5 GHz do 867 Mbps
- Portovi: LAN 1X RJ-45 10/100/1000 Mbps 802.3at/af PoE IN
- Hardverski Watchdog
- Maksimalni broj klijenata 128, preporuceno do 100
- Multi-SSID: 8 SSIDs (do 4 SSIDs po opsegu), VLAN
- Režimi rada: Wi-Fi Router, Access Point, Range Extender, WISP, Client
- Cudy Mesh, Wireless Backhaul, Wired Backhaul, Multi-Band Backhaul
- WAN režimi: DHCP, Static IP, PPPOE, PPTP, L2TP
- QoS, IPv4/IPv6, Multicast, IPTV/VLAN, TTL Customization, IGMP, Forwarding, Firewall
- Captive Portal, VPN Server, Client
- Lokalno upravljenje: Config Web Page, App Control; Daljinsko upravljanje: Config Page via HTTPS, App Control, TR069, TR098, TR111, TR143, TR181
- Radna temperatura -10 °C do 40 °C
- Napajanje DC: 12V=1A, Passive PoE: 24-57V=, PoE: 802.3at/af
- U pakovanju sa AC/DC adapterom 12V=
- Maksimalna potrošnja: PoE 11 W, DC 7,5 W
- Plafonska ili zidna montaza
- Dimenzije $\Phi 231.9 \times 57.1$ mm

<p>MO120106</p>		<p>AP3000 AX3000 Wi-Fi 6 2,4 i 5 GHz Access Point</p> <ul style="list-style-type: none"> - Wi-Fi 2,4 GHz do 574 Mbps, 5 GHz do 2402 Mbps - Portovi: LAN 1X RJ-45 10/100/2500 Mbps 802.3at/af PoE IN - Hardverski Watchdog - Maksimalni broj klijenata 256, preporuceno do 150 - Multi-SSID: 8 SSIDs (do 4 SSIDs po opsegu), VLAN - Režimi rada: Wi-Fi Router, Access Point, Range Extender, WISP, Client - Cudy Mesh, Wireless Backhaul, Wired Backhaul, Multi-Band Backhaul - WAN režimi: DHCP, Static IP, PPPOE, PPTP, L2TP - QoS, IPv4/IPv6, Multicast, IPTV/VLAN, TTL Customization, IGMP, Forwarding, Firewall - Captive Portal, VPN Server, Client - Lokalno upravljenje: Config Web Page, App Control; Daljinsko upravljanje: Config Page via HTTPS, App Control, TR069, TR098, TR111, TR143, TR181 - Radna temperatura -10 °C do 60 °C - Napajanje DC: 12V=1,5A, Passive PoE: 24-57V=, PoE: 802.3at/af - U pakovanju sa AC/DC adapterom 12V= - Maksimalna potrošnja: PoE 12 W, DC 12 W - Plafonska ili zidna montaza - Dimenzije $\Phi 231.9 \times 57.1$ mm 		
-----------------	---	---	--	--

MO120111		<p><u>AP1200 Outdoor AC1200 Wi-Fi 5 2,4 i 5 GHz Access Point</u></p> <ul style="list-style-type: none"> - Wi-Fi 2,4 GHz do 300 Mbps, 5 GHz do 867 Mbps - Portovi: LAN 1X RJ-45 10/100 Passive PoE 24V== - Hardverski Watchdog - Maksimalni broj klijenata 128, preporuceno do 30 - Režimi rada: Wi-Fi Router, Access Point, Range Extender, WISP, Client - WAN režimi: DHCP, Static IP, PPPOE, PPTP, L2TP - QoS, IPv4/IPv6, Multicast, Tag VLAN, TTL Customization, IGMP, Forwarding, Firewall - VPN Client - Lokalno upravljenje: Config Web Page, App Control; Daljinsko upravljanje: Config Page via HTTPS, TR069, TR098, TR111, TR143, TR181 - Radna temperatura -20 °C do 60 °C - Napajanje: Passive PoE: 24V== - U pakovanju sa PoE adapterom 100-240V~ 50/60Hz 24== Passive PoE - Maksimalna potrošnja: 12 W - Montaza na zid ili stub, IP65 kada je vertikalno postavljen - Dimenzije 437×100×53,7 mm 		
RANGE EXTENDER				
MO120105		<p><u>RE300 N300 Wi-Fi 4 2,4 GHz</u></p> <ul style="list-style-type: none"> - Wi-Fi 2,4 GHz do 300 Mbps - Portovi: LAN 1X RJ-45 10/100 - Maksimalni broj klijenata 64, preporuceno do 30 - Režimi rada: Access Point, Range Extender, Client - Cudy Mesh Satellite, Wireless Backhaul, Wired Backhaul, Multi-Band Backhaul - Lokalno upravljenje: Config Web Page, App Control; Daljinsko upravljanje: App Control - Radna temperatura 0 °C do 40 °C - Napajanje AC 100V ~ 240V - Dimenzije 80×60×38 mm 		

MO120104		<p><u>RE1200 AC1200 Wi-Fi 5 2,4 i 5 GHz</u></p> <ul style="list-style-type: none"> - Wi-Fi 2,4 GHz do 300 Mbps, 5GHz do 867 Mbps - Portovi: LAN 1X RJ-45 10/100 - Maksimalni broj klijenata 128, preporuceno do 30 - Režimi rada: Access Point, Range Extender, Client - Cudy Mesh Satellite, Wireless Backhaul, Wired Backhaul, Multi-Band Backhaul - Lokalno upravljanje: Config Web Page, App Control; Daljinsko upravljanje: App Control - Radna temperatura 0 °C do 40 °C - Napajanje AC 100V ~ 240V - Dimenzije 80×60×38 mm 		
MO120103		<p><u>RE1500 AX1500 Wi-Fi 6 2,4 i 5 GHz</u></p> <ul style="list-style-type: none"> - Wi-Fi 2,4 GHz do 300 Mbps, 5GHz do 1201 Mbps - Portovi: LAN 1X RJ-45 10/100 - Maksimalni broj klijenata 128, preporuceno do 30 - Režimi rada: Access Point, Range Extender - Cudy Mesh Satellite, Wireless Backhaul, Wired Backhaul, Multi-Band Backhaul - Lokalno upravljanje: Config Web Page, App Control; Daljinsko upravljanje: App Control - Radna temperatura 0 °C do 40 °C - Napajanje AC 100V ~ 240V - Dimenzije 129,6×80×48,6 mm 		
POE+ INJECTOR				
MO110101		<p><u>POE200 30W GIGABIT POE+ Injector</u></p> <ul style="list-style-type: none"> - Uplink RJ-45 10/100/1000 - Downlink RJ-45 10/100/1000 PoE+ 802.3at/af - Reset taster - Napajanje 100-240V~ 50/60Hz 0.8A - Izlaz 30W, 54V=0.56A - Zaštita od prenaponskih udara, zaštita od elektrostatičkog pražnjenja, zaštita od previsokog napona napajanja, zaštita od kratkog spoja - Napajanje sa uzemljenjem, sa kablom za napajanje - Radna temperatura -10 °C do 40 °C - Moguca montaza na zid - Dimenzije 123×51×35 mm 		

