











Šifra	Slika	Opis		
SWICHEVI				
MO010019		<p>SF1005L 5 portova ethernet switch</p> <ul style="list-style-type: none"> - Portova 5X RJ-45 10/100 Mbps Base-T - Switching Capacity 1 Gbps - Packet Forwarding Rate 0.744 Mpps - Packet Buffer Size 768 kbit - MAC Table Size 2K - Radna temperatura 0 °C do +45 °C - Sa AC/DC adapterom 5V DC, 1A - Dimenzije 86.4 mm × 52 mm × 23 mm 		
MO010012		<p>PFS3008-8ET-L 8 portova ethernet switch</p> <ul style="list-style-type: none"> - Portova 8X RJ-45 10/100 Mbps Base-T - Switching Capacity 1,6 Gbps - Packet Forwarding Rate 1,1904 Mpps - Packet Buffer Size 768 kbit - MAC Table Size 2K - Radna temperatura 0 °C do +45 °C - Sa AC/DC adapterom 5V DC, 1A - Dimenzije 133 mm × 62 mm × 24 mm 		
MO010018		<p>PFS3008-8GT-L 8 portova gigabit ethernet switch</p> <ul style="list-style-type: none"> - Portova 8X RJ-45 10/100/1000 Mbps Base-T - Switching Capacity 16 Gbps - Packet Forwarding Rate 11,904 Mpps - Packet Buffer Size 1,5 Mbit - MAC Table Size 2K - Radna temperatura 0 °C do +45 °C - Sa AC/DC adapterom 5V DC, 1A - Dimenzije 133 mm × 62 mm × 24 mm 		
MO010024		<p>S3024-24GT 24 portova gigabit Layer 2 ethernet switch</p> <ul style="list-style-type: none"> - Portova 24X RJ-45 10/100/1000 Mbps Base-T, portovi 23-24 uplink - Switching Capacity 48 Gbps - Packet Forwarding Rate 35,712 Mpps - Packet Buffer Size 8,4 Mbit - MAC Table Size 16K - DIP switch podesavanje: Default, Port isolation, Port aggregation - Radna temperatura -10 °C do +55 °C - Napajanje 240V AC, 0,4A - Dimenzije 294 mm × 119 mm × 44 mm 		

4-PORT PoE SWICHEVI

<p style="text-align: center;">MO010026</p>		<p><u>PFS3206-4P-96 4 PoE portova ethernet switch 96W</u></p> <ul style="list-style-type: none"> - Portovi: 3X RJ-45 10/100 Mbps Base-T (PoE+), 1X RJ-45 10/100/1000 Mbps Base-T (Hi-PoE), 2X SFP 1000 Mbps Base-X (uplink) - Kaskadno povezivanje preko SFP portova - Switching Capacity 6,8 Gbps - Packet Forwarding Rate 4,91 Mpps - Packet Buffer Size 1 Mbit - MAC Table Size 8K - PoE standard: IEEE802.3af; IEEE802.3at; Hi-PoE (4. port) - PoE snaga: Portovi 1-3 do 30W, port 4 do 60W, ukupno 96W - Radna temperatura -30 °C do +65 °C - Sa AC/DC adapterom 53V DC; - Dimenzije 150 mm × 100 mm × 30 mm 		
<p style="text-align: center;">MO010027</p>		<p><u>PFS3106-4ET-60 4 PoE portova ethernet switch 60W</u></p> <ul style="list-style-type: none"> - Portovi: 4X RJ-45 10/100 Mbps Base-T (PoE), 1X RJ-45 10/100/1000 Mbps Base-T (uplink), 1X SFP 100/1000 Mbps Base-X (uplink) - Switching Capacity 6,8 Gbps - Packet Forwarding Rate 3.57 Mpps - Packet Buffer Size 1 Mbit - MAC Table Size 8K - PoE standard: IEEE802.3af; IEEE802.3at; Hi-PoE (narandžasti port) - PoE snaga: 60W - PoE Wachdog - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -30 °C do +65 °C - Sa AC/DC adapterom 53V DC; podržava backup napajanje - Dimenzije 150 mm × 100 mm × 30 mm 		

MO010027		<p>PFS3006-4ET-36 4 PoE portova ethernet switch 36W</p> <ul style="list-style-type: none"> - Portovi: 4X RJ-45 10/100 Mbps Base-TX (PoE), 2X RJ-45 10/100 Mbps Base-TX (uplink) - Switching Capacity 1,2 Gbps - Packet Forwarding Rate 0,89 Mpps - Jumbo Frame 2048 bzte - MAC Table Size 2K - PoE standard: IEEE802.3af, IEEE802.3at - PoE snaga: Portovi 1-4 do 30W, ukupno 36W - PoE Wachdog - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Napajanje 110-240V AC - Dimenzije 194.0 mm × 108.1 mm × 35.0 mm 		
MO01003		<p>PFS3006-4ET-60 4 PoE portova ethernet switch 60W</p> <ul style="list-style-type: none"> - Portovi: 4X RJ-45 10/100 Mbps Base-T (PoE), 2X RJ-45 10/100 Mbps Base-T (uplink) - Switching Capacity 1,8 Gbps - Packet Forwarding Rate 0,89 Mpps - Packet Buffer Size 1 Mbit - MAC Table Size 8K - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (narandžasti port) - PoE snaga: 60W - PoE Wachdog - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Sa AC/DC adapterom 53V DC - Dimenzije 130 mm × 85 mm × 26 mm 		

<p>MO010001</p>		<p><u>CS4006-4ET-60 Upravljivi (Layer 2) cloud 4 PoE portova ethernet switch 60W</u></p> <ul style="list-style-type: none"> - Portovi: 4X RJ-45 10/100 Mbps Base-T (PoE), 2X RJ-45 10/100/1000 Mbps Base-T (uplink) - Switching Capacity 4,8 Gbps - Packet Forwarding Rate 3,57 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - Jumbo frame: 216 Byte - Port Based VLAN 32, DHCP klijent, WEB & APP menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (narandžasti port) - PoE snaga: Port 1 do 60W, portovi 2-4 do 30W, ukupno do 60W - PoE Wachdog, Loop protection - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Sa AC/DC adapterom 53V DC - Dimenzije 130 mm × 90 mm × 26 mm 		
<p>MO010029</p>		<p><u>CS4006-4GT-60 Upravljivi (Layer 2) Gigabitni cloud 4 PoE portova ethernet switch 60W</u></p> <ul style="list-style-type: none"> - Portovi: 4X RJ-45 10/100/1000 Mbps Base-T (PoE), 2X RJ-45 10/100/1000 Mbps Base-T (uplink) - Switching Capacity 12 Gbps - Packet Forwarding Rate 8,9 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 2K - Jumbo frame: 9216 Byte - Port Based VLAN 32, DHCP klijent, WEB & APP menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port) - PoE snaga: Port 1 do 60W, portovi 2-4 do 30W, ukupno do 60W - PoE Wachdog, Loop protection, PoE Power on/off - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps, moguće samo kada je Managed Mode isključen - Radna temperatura -10 °C do +55 °C - Sa AC/DC adapterom 53V DC - Dimenzije 115 mm × 84 mm × 27 mm 		

8-PORT PoE SWICHEVI


MO010030







CS4010-8ET-60 Upravljivi (Layer 2) cloud

8 PoE portova ethernet switch 60W

- Portovi: 8X RJ-45 10/100 Mbps Base-T (PoE), 2X RJ-45 10/100/1000 Mbps Base-T (uplink)
- Switching Capacity 4,8 Gbps
- Packet Forwarding Rate 3,57 Mpps
- Packet Buffer Size 4 Mbit
- MAC Table Size 8K
- Jumbo frame: 9216 Byte
- Port Based VLAN 32, DHCP klijent, WEB & APP menadžment
- PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (narandžasti port)
- PoE snaga: Port 1 do 60W, portovi 2-8 do 30W, ukupno do 60W
- PoE Wachdog, Loop protection, PoE Power on/off
- Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω /100 m) sa redukcijom brzine do 10 Mbps
- Radna temperatura -10 °C do +55 °C
- Sa AC/DC adapterom 53V DC
- Dimenzije 190 mm × 100 mm × 28 mm

MO010014		<p><u>CS4010-8ET-110 Upravljivi (Layer 2) cloud 8 PoE portova ethernet switch</u></p> <p><u>110W</u></p> <ul style="list-style-type: none"> - Portovi: 8X RJ-45 10/100 Mbps Base-T (PoE), 2X RJ-45 10/100/1000 Mbps Base-T (uplink) - Switching Capacity 5,6 Gbps - Packet Forwarding Rate 4,17 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - Jumbo frame: 9216 Byte - Port Based VLAN 32, DHCP klijent, WEB & APP menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Port 1 do 90W, portovi 2-8 do 30W, ukupno do 110W - PoE Wachdog, Loop protection, PoE Power on/off - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Sa AC/DC adapterom 54V DC - Dimenzije 190 mm × 100 mm × 28 mm 		
----------	---	---	--	--

MO010016		<p><u>CS4010-8GT-110 Upravljivi (Layer 2) Gigabitni cloud 8 PoE portova ethernet switch 110W</u></p> <ul style="list-style-type: none"> - Portovi: 8X RJ-45 10/100/1000 Mbps Base-T (PoE), 2X RJ-45 10/100/1000 Mbps Base-T (uplink) - Switching Capacity 20 Gbps - Packet Forwarding Rate 14,88 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - Jumbo frame: 15K Byte - Port Based VLAN 32, DHCP klijent, WEB & APP menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Port 1 do 90W, portovi 2-8 do 30W, ukupno do 110W - PoE Wachdog, Loop protection, PoE Power on/off - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Sa AC/DC adapterom 54V DC - Dimenzije 190 mm × 106 mm × 30 mm 		
MO010020		<p><u>PFS3010-8ET-65 8 PoE portova ethernet switch 65W</u></p> <ul style="list-style-type: none"> - Portovi: 8X RJ-45 10/100 Mbps Base-TX (PoE), 2X RJ-45 10/100 Mbps Base-TX (uplink) - Switching Capacity 2 Gbps - Packet Forwarding Rate 1,49 Mpps - MAC Table Size 2K - Jumbo frame: 2048 Byte - PoE standard: IEEE802.3af/ IEEE802.3at - PoE snaga: Portovi 1-8 do 30W, ukupno do 65W - PoE Wachdog - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Napajanje 110 - 240V DC - Dimenzije 243 mm × 123 mm × 35 mm 		

MO010010		<p><u>PFS3110-8ET-96 8 PoE portova ethernet switch 96W</u></p> <ul style="list-style-type: none"> - Portovi: 8X RJ-45 10/100 Mbps Base-T (PoE), 1X RJ-45 10/100/1000 Mbps Base-T (uplink), 1 × SFP 1000 Mbps (uplink) - Switching Capacity 7,6 Gbps - Packet Forwarding Rate 4,17 Mpps - Packet Buffer Size 1 Mbit - MAC Table Size 8K - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Portovi 1-2 do 90W, Portovi 3-8 do 30W, ukupno do 96W - PoE Wachdog - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -30 °C do +65 °C - Sa AC/DC adapterom 54V DC - Dimenzije 150 mm × 100 mm × 42 mm 		
MO010025		<p><u>PFS3211-8GT-120 8 PoE portova Gigabitni ethernet switch 120W</u></p> <ul style="list-style-type: none"> - Portovi: 8X RJ-45 10/100/1000 Mbps Base-T (PoE), 1X RJ-45 10/100/1000 Mbps Base-T (uplink), 2 × SFP 1000 Mbps (uplink) - Switching Capacity 33 Gbps - Packet Forwarding Rate 16,37 Mpps - Packet Buffer Size 1,75 Mbit - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Portovi 1-2 do 90W, Portovi 3-8 do 30W, ukupno do 120W - PoE Wachdog - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -30 °C do +65 °C - Sa AC/DC adapterom 54V DC - Dimenzije 150 mm × 110 mm × 42 mm 		


16-PORT PoE SWICHEVI


MO010013




S3218-16ET-135 16 PoE portova ethernet switch 135W

- Portovi: 16X RJ-45 10/100 Mbps Base-T (PoE), 2X RJ-45 10/100/1000 Mbps (Combo), 2 × SFP 1000 Mbps (Combo)
- Switching Capacity 7,2 Gbps
- Packet Forwarding Rate 5,36 Mpps
- Packet Buffer Size 4 Mbit
- MAC Table Size 8K
- Jumbo frame: 15K Byte
- PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port)
- PoE snaga: Portovi 1-2 do 90W, Portovi 3-16 do 30W, ukupno do 135W
- PoE Watchdog, Port isolation, VIP port (port 1 do 8)
- Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps
- Radna temperatura -10 °C do +55 °C
- Napajanje 230V AC
- Dimenzije 440 mm × 220 mm × 44 mm

MO010002		<p><u>CS4218-16ET-135 Upravljivi (Layer 2) cloud 16 PoE portova ethernet switch 135W</u></p> <ul style="list-style-type: none"> - Portovi: 16X RJ-45 10/100 Mbps (PoE), 2X RJ-45 10/100/1000 Mbps (Combo), 2 x SFP 1000 Mbps (Combo) - Switching Capacity 7,2 Gbps - Packet Forwarding Rate 5,36 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - Jumbo frame: 15K Byte - Port Based VLAN 32, DHCP klijent, WEB & APP menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Portovi 1-2 do 90W, Portovi 3-16 do 30W, ukupno do 135W - PoE Wachdog, Loop protection, PoE Power on/off - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Napajanje 230V AC - Dimenzije 440 mm x 220 mm x 44 mm 		
----------	---	--	--	--

MO010017		<p><u>CS4218-16ET-240 Upravljivi (Layer 2) cloud 16 PoE portova ethernet switch 240W</u></p> <ul style="list-style-type: none"> - Portovi: 16X RJ-45 10/100 Mbps Base-T (PoE), 2X RJ-45 10/100/1000 Mbps (Combo), 2 × SFP 1000 Mbps (Combo) - Switching Capacity 7,2 Gbps - Packet Forwarding Rate 5,36 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - Jumbo frame: 15K Byte - Port Based VLAN 32, DHCP klijent, WEB & APP menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Portovi 1-2 do 90W, Portovi 3-16 do 30W, ukupno do 240W - PoE Wachdog, Loop protection, PoE Power on/off - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Napajanje 230V AC - Dimenzije 440 mm × 220 mm × 44 mm 		
----------	---	---	--	--

MO010022		<p><u>CS4220-16GT-240 Upravljivi (Layer 2) cloud 16 PoE portova Gigabitni ethernet switch 240W</u></p> <ul style="list-style-type: none"> - Portovi: 16X RJ-45 10/100/1000 Mbps (PoE), 2X RJ-45 10/100/1000 Mbps (Uplink), 2 x SFP 1000 Mbps (Uplink) - Switching Capacity 40 Gbps - Packet Forwarding Rate 29,76 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - Jumbo frame: 15K Byte - Port Based VLAN 32, DHCP klijent, WEB & APP menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Portovi 1-2 do 90W, Portovi 3-16 do 30W, ukupno do 240W - PoE Wachdog, Loop protection, PoE Power on/off - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Napajanje 230V AC - Dimenzije 440 mm × 220 mm × 44 mm 		
----------	---	---	--	--

24-PORT PoE SWICHEVI

MO010006



CS4226-24ET-240 Upravljivi (Layer 2) cloud 24 PoE portova ethernet switch


240W


- Portovi: 24X RJ-45 10/100 Mbps (PoE), 2X RJ-45 10/100/1000 Mbps (Combo), 2 x SFP 1000 Mbps (Combo)
- Switching Capacity 8,8 Gbps
- Packet Forwarding Rate 6,55 Mpps
- Packet Buffer Size 4 Mbit
- MAC Table Size 8K
- Jumbo frame: 15K Byte
- Port Based VLAN 32, DHCP klijent, WEB & APP menadžment
- PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port)
- PoE snaga: Portovi 1-2 do 90W, Portovi 3-24 do 30W, ukupno do 240W
- PoE Wachdog, Loop protection, PoE Power on/off
- Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps
- Radna temperatura -10 °C do +55 °C
- Napajanje 230V AC
- Dimenzije 440 mm x 220 mm x 44 mm

**CS4228-24GT-240 Upravljivi (Layer 2)
cloud 24 PoE portova Gigabitni ethernet
switch 240W**




- Portovi: 24X RJ-45 10/100/1000 Mbps (PoE), 2X RJ-45 10/100/1000 Mbps (Uplink), 2 x SFP 1000 Mbps (Uplink)
- Switching Capacity 56 Gbps
- Packet Forwarding Rate 41,66 Mpps
- Packet Buffer Size 4 Mbit
- MAC Table Size 8K
- Jumbo frame: 15K Byte
- Port Based VLAN 32, DHCP klijent, WEB & APP menadžment
- PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port)
- PoE snaga: Portovi 1-2 do 90W, Portovi 3-24 do 30W, ukupno do 240W
- PoE Wachdog, Loop protection, PoE Power on/off
- Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps
- Radna temperatura -10 °C do +55 °C
- Napajanje 230V AC
- Dimenzije 440 mm × 220 mm × 44 mm


MO010015		<p><u>CS4228-24GT-375 Upravljivi (Layer 2) cloud 24 PoE portova Gigabitni ethernet switch 375W</u></p> <ul style="list-style-type: none"> - Portovi: 24X RJ-45 10/100/1000 Mbps (PoE), 2X RJ-45 10/100/1000 Mbps (Uplink), 2 x SFP 1000 Mbps (Uplink) - Switching Capacity 56 Gbps - Packet Forwarding Rate 41,66 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - Jumbo frame: 15K Byte - Port Based VLAN 32, DHCP klijent, WEB & APP menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Portovi 1-2 do 90W, Portovi 3-24 do 30W, ukupno do 375W - PoE Wachdog, Loop protection, PoE Power on/off - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Napajanje 230V AC - Dimenzije 440 mm × 220 mm × 44 mm 		
----------	---	---	--	--

MO010015		<p>S4228-24GT-375 Upravljivi (Layer 2) 24 PoE portova Gigabitni ethernet switch 360W</p> <ul style="list-style-type: none"> - Portovi: 24X RJ-45 10/100/1000 Mbps (PoE), 2X RJ-45 10/100/1000 Mbps, 2 × SFP 1000 Mbps, 1X Console - Switching Capacity 56 Gbps - Packet Forwarding Rate 41,664 Mpps - Packet Buffer Size 4 Mbit - MAC Table Size 8K - Jumbo frame: 10K Byte - Port Based VLAN 10, DHCP klijent, DHCP Server, DHCP Snooping, WEB menadžment - PoE standard: IEEE802.3af/ IEEE802.3at/ Hi-PoE (crveni port)/ IEEE802.3bt (crveni port) - PoE snaga: Portovi 1-2 do 90W, Portovi 3-24 do 30W, ukupno do 360W - PoE Wachdog, PoE Power on/off - Do 250m PoE transmisija (CAT5E/CAT6. max. DC otpornost < 10 Ω/100 m) sa redukcijom brzine do 10 Mbps - Radna temperatura -10 °C do +55 °C - Napajanje 230V AC - Dimenzije 440 mm × 300 mm × 44 mm 		
----------	---	---	--	--


SFP SWICHEVI



MO010028		<p>PFS5936-24GF8GT4XF 24-portni 1G SFP upravljivi (Layer 2+) Gigabitni switch sa 4 porta 10G SFP+</p> <ul style="list-style-type: none"> - Portovi: 24X opticki 100/1000 Mbps, 8X RJ-45 10/100/1000 Mbps, 4X opticki SFP+ 1/10 Gbps, 1X Console - Switching Capacity 144 Gbps - Packet Forwarding Rate 107 Mpps - Packet cache 32MB - MAC Table Size 32K - Static MAC Adress 256 - VLAN Amount 4K - Router ports 128 - DHCP klijent, DHCP Server, DHCP Snooping, WEB menadžment - Loop protection, Link aggregation, Flow control, Port mirroring, Ring network - Radna temperatura -20 °C do +55 °C - Napajanje 230V AC - Dimenzije 360 mm × 440 mm × 43.6 mm 		
----------	---	--	--	--

PoE EXTENDERI

PF030013		<p><u>PFT1300 PoE extender sa jednim PoE ulazom i dva PoE izlaza</u></p> <ul style="list-style-type: none"> - 1X RJ-45 10/100M PoE ulaz; 1X RJ-45 10/100M PoE izlaz za IP kameru; 1X RJ-45 10/100M PoE izlaz ka sledecem extenderu - Podrzava pasivno PoE kaskadno povezivanje napajanja i podataka - IEEE 802.3af/at standard za napajanje IP kamera - Radna temperatura -30 °C do +65 °C - Montaza na DIN sinu - Dimenzije 79mm × 52mm × 23mm 		
----------	---	--	--	--

WiFi ROUTER

MO010102		<p><u>DH-AC12 AC1200 Wireless router</u></p> <ul style="list-style-type: none"> - 1×10/100/1000 Mbps WAN Port 3×10/100/1000Mbps LAN Port - Wireless standard: 2,4 GHz: IEEE 802.11b/g/n 5 GHz: IEEE 802.11a/n/ac - Wireless brzina prenosa: 2,4 GHz: 300 Mbps 5 GHz: 867 Mbps - Radne frekvencije: 2,4 GHz: 2,400 GHz–2,484 GHz 5 GHz: 5,150 GHz–5,850 GHz - Sirina kanala: 2,4 GHz: 20/40 MHz, 5 GHz: 20/40/80 MHz - PPPoE; Dynamic IP; Static IP, - Wireless Router Mode, Wireless Relay Mode (Client+AP) - Poluprecnik pokrivenosti: 15m, optimalno 7m - Broj prijavljenih uređaja: 2,4 GHz:32, 5 GHz: 32 - Radna temperatura 0 °C do +40 °C - Napajanje 12- Radna temperatura -10 °C do +55 °C - Napajanje AC/DC adapter 12V DC, 1A - Dimenzije 220 mm × 144 mm × 179 mm 		
----------	---	--	--	--

MO010101		<p><u>DH-AX15M AX1500 Wireless router</u></p> <ul style="list-style-type: none"> - 1x10/100/1000 Mbps WAN Port 2x10/100/1000Mbps LAN Port - Wireless standard: 2,4 GHz: IEEE 802.11b/g/n 5 GHz: IEEE 802.11a/n/ac/ax - Wireless brzina prenosa: 2,4 GHz: 300 Mbps 5 GHz: 1201 Mbps - Radne frekvencije: 2,4 GHz: 2,412 GHz–2,484 GHz 5 GHz: 5,150 GHz–5,850 GHz - Sirina kanala: 2,4 GHz: 20/40 MHz, 5 GHz: 20/40/80 MHz - PPPoE; Dynamic IP; Static IP, - Wireless Router Mode, Wireless Relay Mode (Extender) - Parental Controls - Broj prijavljenih uredjaja: 2,4 GHz:16, 5 GHz: 32 - Radna temperatura 0 °C do +40 °C - Napajanje AC/DC adapter 12V DC, 1A - Dimenzije 215 mm × 119 mm × 173 mm 		
MO010103		<p><u>DH-N3 N300 Wireless router</u></p> <ul style="list-style-type: none"> - 1x10/100 Mbps WAN Port 2x10/100Mbps LAN Port - Wireless standard: 2,4 GHz: IEEE 802.11b/g/n - Wireless brzina prenosa: 2,4 GHz: 300 Mbps - Radne frekvencije: 2,4 GHz: 2,412 GHz–2,484 GHz - Sirina kanala: 2,4 GHz: 20/40 MHz, - Poluprecnik pokrivenosti: 15m, optimalno 7m - PPPoE; Dynamic IP; Static IP, - Wireless Router Mode, Wireless Relay Mode (Extender) - Broj prijavljenih uredjaja: 2,4 GHz: 32 - Radna temperatura 0 °C do +40 °C - Napajanje AC/DC adapter 12V DC, 1A - Dimenzije 149 mm × 126 mm × 174 mm 		