

DAHUA VIDEO INTERCOM

Easy to install, Easy to use



Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
Dahua Interfonski Kompleti				
IN010008		<u>KTA02 Analogni video-interfon</u> - 4-žilni komplet - pozivna jedinica sa jednim tasterom - MZ kombinacijom i kamerom, 1.3MP - horizontalni ugao 70° - Monitor, 7" rezolucija - Dimenzije 131.45mm x 46.00mm x 33.80mm - Radna temperatura -30°C do +60°C - IP66 Sertifikovan		
IN010009		<u>KTP01 IP video-interfon DHI-VTO2202F-P+ DHI-VTH2421FW-P</u> - IP Villa Door Station VTO2202F-P - 2MP CMOS kamera - Mehaničko dugme - Materijal Aluminijum - Micro SD, Max 64 GB - Ugao kamera 160° - Dimenzije spoljne jedinice 130 mm x 96 mm x 28.5 mm - IP65 IK07 sertifikovan - 7-inch TFT monitor DHI-VTH2421FW-P - Dimenzije monitora 119.6 mm x 221.5 mm x 21.5 mm		

IN010005		KTP02 IP video-interfon DHI-VTO2111D-P-S3 + DHI-VTH2421FB-P + DH-PFS3006-4ET-36 - IP Villa Door StationVTO2111D-P-S3 - 2MP CMOS kamera - Two-way audio - Mifare čitač - Materijal PC + Acrylic - Nazidna montaža - Dimenzije spoljne jedinice 135.1mm × 70.6mm × 34.6mm - IP65 IK04 sertifikovan - 7-inchTFT monitor DHI-VTH2421FB-P - Demenzije monitora 119.6 mm × 221.5 mm × 21.5 mm		
IN010007		KTP03 IP video-interfon DHI-DHI-VTO2111D-P-S3+DHI-VTH2621G-P+DH-PFS3006-4ET-36 - IP Villa Door StationVTO2111D-P-S3 - 2MP CMOS kamera - Two-way audio - Mifare čitač - Materijal PC + Acrylic - Nazidna montaža - Dimenzije spoljne jedinice 135.1mm × 70.6mm × 34.6mm - IP65 IK04 sertifikovan - 7-inchTFT monitor DHI-VTH2421FB-P - Demenzije monitora 189.6 mm × 134.6 mm × 26.0 mm		
IN010006		KTX01 - 2-žilni WiFi hibridni video interfonski komplet - VTO2003F pozivni panel - 2MPX kamerom - Dimenzije 130mm × 96mm × 28.5mm, - Radna temperatura-40°C do +60°C, - Sertifikovan IP67, IK10 - VTH5123H-W 2-žilni 7"" monitor sa WiFi-jem, 7" - Dimenzije 130mm × 189mm × 23.9mm,		

IN010020		<u>VDKP01-WG</u> - WiFi video zvono sa unutrasnjim bezicnim zvonom i jednim tasterom za pozivanje, zvucnikom i mikrofonom na spoljasnjoj jedinici - 4MPX kamera fisheye - PIR detekcija pokreta, 2 IR LED, AI detekcija ljudi i vozila - WiFi 6, konekcija na 2,4GHz - Podrzava SD memorijske kartice do 256 GB - DMSS aplikacija - Uparivanje preko Bluetooth - Jedno zvono se moze povezati sa vise spoljasnjih jedinica - Napajanje spoljasnje jedinice: USB 5 VDC±5% 2 A ili spoljasnje napajanje 10–24 VDC ili 14–24 VAC 1 A - Napajanje unutrasnje jedinice: 100–240 VAC 50/60 Hz - Sertifikovan IP65 - Dimenzije spoljasnje jedinice 135 mm × 45 mm × 24.2 mm		
Dahua Interfonske pozivne table				
IN010004		<u>VTO2111D-P-S3</u> - 2MP SIP video interfonska pozivna jedinica sa čitačem, - Vidni ugao 107° H, - Kapaciteta do 10.000 kartica, - Opseg radne temperature -30°C do +60°C, - IP65, IK04 - Dimenzije 135.1mm × 70.6mm × 34.6mm;		
IN010010		<u>VTO2202F-P-S3</u> - 2MP SIP pozivni panel za IP i 2-žilne IP video interfonske sisteme, - Vidni ugao 168.6°, - IP65, IK07; Aluminijsko kućište, - Opseg radne temperature od -30°C do +60°C, - Radna temperatura –30°C~+60°C, - Dimenzije 130mm×96mm×28.5mm, - Potrebna dozna VTM114 ili nazidna dozna VTM115 ili VTM05R.		

IN010003		<u>VTO2211G-WP</u> - 2MP SIP video interfonska pozivna jedinica, WiFi, sa čitačem, - Kapaciteta do 10.000 kartica, - Nazidna montaža, - Opseg radne temperature -30°C do +60°C, - Dimenzije 150mm ×100mm ×25.4mm		
IN010012		<u>VTO2311R-WP</u> - 2MP SIP pozivni panel za IP video interfonske sisteme, - vidni ugao 110°, - IP65 stepen zaštite, - Plastično kućište, - Radna temperatura od -40°C do +60°C, - Micro SD card slot, - Dimenzije 160mm × 50mm × 30mm		
IN010001		<u>VTO3311Q-WP</u> - 2MP SIP Vandal-proof pozivni panel za IP video interfonske sisteme, - WDR 120dB, - Dimenzije 188.1mm × 107.2mm × 30mm, - IP65 stepen zaštite; IK08 - Metalno kućište; - Radna temperatura od -40°C do +60°C		
IN010001		<u>VTO3222E-P</u> - 2MP Pozivni panel za IP video interfonske sisteme, - WDR 120dB, - Dimenzije 200.0 mm × 98.0 mm × 35.4 mm, - IP65 stepen zaštite; IK08, - Aluminijsko kućište; - Radna temperatura od -40°C do +60°C, - Pripadajuća dozna VTM08R, VTM116-01, VTM117		

IN010002		<u>VTO6521H-S2</u> - 2MPX IP digitalni video interfonski pozivni panel sa čitačem i tastaturom, - WDR 120dB, - Ugrađena mikro-zvučna kombinacija, - Dimenzije 388.5 mm × 145.5 mm × 43.5 mm, - IP65 stepen zaštite, - Radna temperatura -30°C do +60°C, - Potrebna dozna VTM121, VTM130		
		<u>VTO6531H-S2</u> - 2MPX IP digitalni video interfonski pozivni panel sa čitačem i tastaturom, i funkcijom prepoznavanja lica, - WDR 120dB, - Ugrađena mikro-zvučna kombinacija, - Dimenzije 388.5 mm × 145.5 mm × 43.5 mm, - IP65 stepen zaštite, - Radna temperatura -30°C do +60°C, - Potrebna dozna VTM121, VTM130		
Dahua Video Monitori				
IN010105		<u>VTH2611L-WP</u> - P SIP 2.0 video intercom hands-free monitor, touch-screen, - 4.3" TFT LCD, - Pozivanje kroz imenik, - Rezolucija 480x272 piksela, - Dimenzije 136.0mm × 140.0mm × 25.5mm , - 4 alarmna ulaza, 1 alarmni izlaz.		
IN010102		<u>VTH2421FW-P</u> - IP video intercom hands-free monitor, touch-screen, - 7" TFT LCD, - pozivanje kroz imenik, - Snapshot i Video snimanje; Micro SD slot (maks. 32GB), - Dimenzije 119.6mm × 221.5mm × 21.5mm - 6 alarmnih ulaza, 1 alarmni izlaz.		

IN010100		<u>VTH2621GW-P</u> - IP SIP 2.0 video intercom hands-free monitor, touch-screen, - 7" TFT LCD, - Dimenzije 189.6 mm × 134.6 mm × 26.0 mm , - 6 alarmnih ulaza, 1 alarmni izlaz, - Ulaz za zvono, - Bele boje.		
IN010101		<u>VTH2621G-WP</u> - IP SIP 2.0 video intercom hands-free monitor, touch-screen, - 7" TFT LCD, - Dimenzije 189.6 mm × 134.6 mm × 26.0 mm , - 6 alarmnih ulaza, 1 alarmni izlaz, - Ulaz za zvono, - Crne boje.		
IN010104		<u>VTH2621GW-WP</u> - IP SIP 2.0 video intercom hands-free monitor, touch-screen, WiFi, - 7" TFT LCD, - Dimenzije 189.6 mm × 134.6 mm × 26.0 mm , - 6 alarmnih ulaza, 1 alarmni izlaz, - Ulaz za zvono, - Crne boje.		
IN010103		<u>VTH5221D-S2</u> - IP Wi-Fi video intercom hands-free monitor, - 7" TFT LCD, - Dimenzije 215x140x21mm, - 6 alarmnih ulaza, 1 alarmni izlaz, - Radna temperatura od -10°C do 55°C; - - Crne boje		
IN010106		<u>VTH5321GW-W</u> - IP SIP 2.0 video intercom hands-free monitor, touch-screen, - 7" TFT LCD, - Dimenzije 189.6mm ×134.6mm ×26mm, - 8 alarmnih ulaza, 1 alarmni izlaz, - Potrebno napajanje 12VDC direktno ili standardni PoE, 7W, - Bele boja		

Dodatna oprema				
IN010205		<u>DEE1010B-S2</u> - Modul za dodatnu bravu/čitač,		

