
















Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
KAMERE HDCVI 2MPX				
VND01001		<p><u>Dahua HAC-B1A21-U-0360B</u></p> <ul style="list-style-type: none"> - 2MP Bullet IC kamera, - 3.6mm F2.0 fiksni objektiv, - Vidni ugao 80° H, - Smart IC diode dometa cca. 30m, - Plastično kućište, - Dimenzije 146.1mm × 70.0 mm × 69.8mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/2.8W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		
VND01030		<p><u>Dahua HAC-T1A21-U-0280B</u></p> <ul style="list-style-type: none"> - 2MP dome IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC LE diode dometa cca. 25m, - Plastično kućište, - Dimenzije Ø85.0 mm × 77.1 mm, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%, - Pripadajuće dozne PFA12C 		
VND01002		<p><u>Dahua HAC-B2A21-U-0360B</u></p> <ul style="list-style-type: none"> - 2MP bullet IC kamera, - 3.6mm F2.0 fiksni objektiv, - Vidni ugao 80° H, - Smart IC LE diode dometa cca. 30m, - Metalno kućište, - Dimenzije 150.0 mm × 69.7 mm × 70.0 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDC ±30%/2.8W, - Pripadajuće dozne PFA130-E, PFA152-E. 		




VND01031		<p><u>Dahua HAC-T2A21-U-0280B</u></p> <ul style="list-style-type: none"> - 2MP eyeball IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC LE diode dometa cca. 30m, - Metalno kućište, - Dimenzije $\Phi 94.0$ mm \times 77.9 mm, - Radna temperatura $-40^{\circ}\text{C}\sim+60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 12VDC $\pm 30\%$/2.8W, - Pripadajuće dozne PFA13-A, PFB205W, PFA152-E, PFA106, PFB220C. 		
VND01013		<p><u>Dahua HAC-HFW1200C-0280B</u></p> <ul style="list-style-type: none"> - 2MP bullet IC kamera, - 2.8mm F1.9 fiksni objektiv, - Vidni ugao 102° horizontalno, - Smart IC LE diode dometa cca. 30m, - Plastično kućište, - Dimenzije 161.3mm \times 69.7mm \times 70.0mm, - Radna temperatura $-40^{\circ}\text{C}\sim+60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 12VDC $\pm 30\%$/2.8W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		
VND01017		<p><u>Dahua HAC-HFW1200T-0280B</u></p> <ul style="list-style-type: none"> - 2MP bullet IC kamera, - 2.8mm fiksni objekti, - Vidni ugao 102° H, - Smart IC SMD LE diode dometa cca. 30m, - Metalno kućište, - Dimenzije 174.5 mm \times 70.6 mm \times 72.3 mm, - Radna temperatura $-40^{\circ}\text{C}\sim+60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 12VDC/3.2W, - Pripadajuće dozne PFA134, PFA152-E. 		




VND01019		<p><u>Dahua HAC-HFW1200TL-0360B</u></p> <ul style="list-style-type: none"> - 2MP bullet IC kamera, - 3.6mm F1.85 fiksni objektiv, - Vidni ugao 83° H, - Smart IC LE diode dometa cca. 40m, - - Kućište od plastike, - Dimenzije 80.2mm×76.2mm×198.9mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12V ±30% DC/2.8 W, - Pripadajuće dozne PFA134, PFA152-E, PFA12A. 		
VND01032		<p><u>Dahua HAC-HFW1200TL-A-0360B</u></p> <ul style="list-style-type: none"> - 2MP bullet IC kamera, - 3.6mm F1.85 fiksni objektiv, - Vidni ugao 84° H, - Smart IC LE diode dometa cca. 80m, - Integrisan mikrofoni, - Kućište od metala i plastike, - Dimenzije 80.2mm×76.2mm×198.9mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12V ±30% DC/ 4.9W, - Pripadajuće dozne PFA134, PFA152-E, PFA12A. 		
VND01014		<p><u>Dahua HAC-HFW1200CM-IL-A-0360B</u></p> <ul style="list-style-type: none"> - 2MP bullet sa hibridnim iluminatorima, - 3.6mm F2.0 fiksni objektiv, - Vidni ugao 83° H, - IC i Bele LE diode dometa 20m, - Integrisan mikrofoni, - Metalno kućište, - Dimenzije 166.6mm × 69.7mm × 70mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /2.6W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 		




VN01021		<p><u>Dahua HAC-HFW1200CL-IL-A-0360B</u></p> <ul style="list-style-type: none"> - 2MP Bullet sa hibridnim iluminatorima, - 3.6mm F2.0 fiksni objektiv, - Vidni ugao 83° H, - IC i Bele LE diode dometa 20m , - Integrisan mikrofoni, - Plastično kućište, - Dimenzije 163.4mm × 69.7mm × 70mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /2.6W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 		
VND01020		<p><u>Dahua HAC-HFW1200TLM-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 2MP bullet sa hibridnim iluminatorima, - Objektiv 2.8mm, - Vidni ugao 102° , - IC i Bele LE diode dometa 40m, - Integrisan mikrofoni, - Metalno i plastično kućište, - Dimenzije 198.4mm × 80.2mm × 76.2mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /4.1W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 		
VND01018		<p><u>Dahua HAC-HFW1200TH-I8-A-0360B</u></p> <ul style="list-style-type: none"> - 2MP bullet IC kamera, - 3.6mm F2.0 fiksni objektiv, - Vidni ugao 83° H, - Smart IC LE diode dometa cca. 80m, - Metalno i plastično kućište, - IP67 Sertifikovano - Dimenzije 240.7 mm × 90.7 mm × 90.4 mmm, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/6W, - Pripadajuće dozne PFA130-E, PFA152-E. 		

VND01015		<p><u>Dahua HAC-HFW1200D-0360B</u></p> <ul style="list-style-type: none"> - 2MP bullet IC kamera, - 3.6mm fiksni objektiv, - Vidni ugao 83° H, - Smart IC LE diode dometa cca. 80m, - Metalno kućište, - Dimenzije 241.8mm×90.4mm×90.4mmmm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC/6.8W, - Pripadajuće dozne PFA130-E, PFA152-E. 		
VND01016		<p><u>Dahua HAC-HFW1200R-Z-A-2712</u></p> <ul style="list-style-type: none"> - 2MP bullet kamera, - 2.7~12mm F1.6 motorizovani zum, - Podesivi vidni ugao 28.3°~98.2°H, - Smart IC LE diode dometa cca. 80m, - Integrisan mikrofoni, - Kućište od metala, - IP67 sertifikovana, - Radna temperatura -30°C~+60°C, - Dimenzije 209.6mm × 90.4mm ×90.4mm, - Napajanje 12VDC ±30%/9.4W, - Pripadajuće dozne PFA13-G, PFA130-E, PFA152-E. 		
VND01084		<p><u>Dahua HAC-HFW1200RM-IL-T-0280B</u></p> <ul style="list-style-type: none"> - 2MP bullet kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 113° horizontalno, - Bele i IC LE diode dometa cca. 30m, - Metalno kućište, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije 166.4 mm × 69.7 mm × 70.0 mm, - Napajanje 12VDC ±30%/9.37W, - Pripadajuće dozne PFA130-E, PFA134, PFA151. 		

VND01096		<p><u>Dahua HAC-HFW1249X-A-PRO-0280B</u></p> <ul style="list-style-type: none"> - 2MP bullet kamera sa WizColor+AI-ISP tehnologijom, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 101° horizontalno, - Bele i IC LE diode dometa cca. 50m, - Detekcija pokreta (kroz XVR) - Super Adapt - Inkorporirana 2 mikrofona - DWDR, BLC, HLC, 3D DNR - Maskiranje (do 8 zona) - Ugradjen mikrofon (CVI) - Metalno i plastično kućište, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije 166.4 mm × 69.7 mm × 70.0 mm, - Napajanje 12VDC ±30%/5.6W, - Pripadajuće dozne PFA130-E, PFA134, PFA151. 		
VND01041		<p><u>Dahua HAC-HDW1200CLQ-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102° H , - Bele i IC LE diode dometa cca. 20m, - Integrisan mikrofon, - Plastično kućište, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije Ø97.1mm × 93.8mm, - Napajanje 12VDC ±30% /2.6W, - Pripadajuće dozne PFA13-G, PFB205W-E, PFA152-E. 		
VND01006		<p><u>Dahua HAC-HDW1200TRQ-0280B</u></p> <ul style="list-style-type: none"> - 2MP dome IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102° horizontalno, - Smart IC LE diode dometa cca. 30m, - Plastično kućište, - IP50 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije Ø97.1 mm × 93.0 mm, - Napajanje 12VDC ±30%/2.7W, - Pripadajuće dozne PFA13-G, PFB205W-E, PFA152-E, PFA109. 		

VND01090		<p><u>Dahua HAC-HDBW1231EA-A-0280</u></p> <ul style="list-style-type: none"> - 2MP dome anti vandal IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102° horizontalno, - Smart IC LE dioda dometa cca. 40m, - Starlight, 130 dB true WDR, 3D NR - Metalno kućište, - P67 i IK10 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije Φ112.0 mm × 89.1 mm - Napajanje 12VDC \pm30%/2.7W, - Pripadajuće dozne PFA136, PFB2202W, PFA1E2-E, PFA1E1 		
VND01004		<p><u>Dahua HAC-HDW1200TLM-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102°, - Smart IC dometa cca. 30m, - Metalno kućište, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije Φ94.0 mm × 85.7 mm, - Napajanje 12VDC \pm30% /3.2W, - Pripadajuće dozne PFA13A-E, PFB205W-E, PFA152-E. 		
VND01042		<p><u>Dahua HAC-HDW1200TLM-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102° H , - Bele i IC LE diode dometa cca. 20m, - Integrisan mikrofon, - Metalno kućište, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije Φ97.1mm × 93.8mm, - Napajanje 12VDC \pm30% /2.6W, - Pripadajuće dozne PFA13A-E, PFB205W-E, PFA152-E. 		

VND01046		<p><u>Dahua HAC-HDW1200TLM-IL-A-0280B- BLACK</u></p> <ul style="list-style-type: none"> - 2MP dom kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102° H, - Bele i IC LE diode dometa cca. 20m, - Integrisan mikrofon, - Metalno kućište, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije $\Phi 97.1\text{mm} \times 93.8\text{mm}$, - Napajanje 12Vdc $\pm 30\%$ /2.6W, - Pripadajuće dozne PFA13A-E, PFB205W-E, PFA152-E. 		
VND01005		<p><u>Dahua HAC-HDW1200T-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102° H, - Bele i IC LE diode dometa cca. 40m, - Integrisan mikrofon, - Metalno kućište, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije $\Phi 106.0\text{ mm} \times 99.2\text{mm}$, - Napajanje 12Vdc $\pm 30\%$ /4.1W, - Pripadajuće dozne PFA130-E, PFB204W, PFA152-E. 		
VND01083		<p><u>Dahua HAC-HDW1200TQ-IL-T-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 111.3° H, - Bele i IC LE diode dometa cca. 40m, - Integrisan mikrofon i zvučnik, - dvosmerna komunikacija - Metalno i plastično kućište, - DWDR, BLC, HLC, 3D DNR, OSD - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije $\Phi 106.0\text{ mm} \times 99.2\text{mm}$, - Napajanje 12Vdc $\pm 30\%$ /9.37W, - Pripadajuće dozne PFA13G, PFA152-E, PFB2203W, PFA150. 		

VND01095		<p><u>Dahua HAC-HDW1249X-A-PRO-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom kamera sa WizColor+AI-ISP tehnologijom, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 101° horizontalno, - Bele i IC LE diode dometa cca. 50m, - Detekcija pokreta (kroz XVR) - Super Adapt - Inkorporirana 2 mikrofona - DWDR, BLC, HLC, 3D DNR - Maskiranje (do 8 zona) - Ugradjen mikrofon (CVI) - Metalno i plastično kućište, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Dimenzije $\Phi 109.9 \text{ mm} \times 102.2 \text{ mm}$ - Napajanje 12VDC $\pm 30\%/5.6W$, - Pripadajuće dozne PFB2203, PFA13G, PFA150-V2, PFA152-E. 		
VND010035		<p><u>Dahua HAC-HDW1200T-Z-A-2712</u></p> <ul style="list-style-type: none"> - 2MP dom kamera, - 2.7~12mm F1.7 motorizovani zum objektiv, - Podesivi vidni ugao 28.3°~98.2°,H - Smart IC LE diode dometa cca. 60m, - Integrisan mikrofon, - Metalno kućište, - IP67 sertifikovana, - Radna temperatura -30°C~+60°C, - Dimenzije $\phi 122\text{mm} \times 104.8\text{mm}$, - Napajanje 12VDC $\pm 30\%/8.2W$, - Pripadajuće dozne PFA137, PFA130-E, PFB203W, PFA152-E. 		
VND01034		<p><u>Dahua HAC-HUM3200A-0280</u></p> <ul style="list-style-type: none"> - 2MP IC kamera u kućištu detektora - 2.8mm fiksni objektiv, - Vidni ugao 105° H, - IC dometa cca. 10m, - Integrisan mikrofon, - Kućište od plastike, - Radna temperatura -40°C~+60°C, - Dimenzije 61.7mm \times 58.1mm \times 119.7mm, - Napajanje 12VDC $\pm 30\%/3,3W$, 		