

















Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
KAMERE HDCVI 5MPX				
VND01050		<p><u>Dahua HAC-B1A51-U-0280B</u></p> <ul style="list-style-type: none"> - 5MP Bullet IC kamera, - 2.8mm F2.0 fiksni objektiv, - Smart IC diode dometa cca. 30m, - Plastično kućište, - Dimenzije 146.1mm × 70.0 mm × 69.8mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/3,7W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		
VND01052		<p><u>Dahua HAC-HAC-T1A51U-0280B</u></p> <ul style="list-style-type: none"> - 5MP dome IC kamera, - fiksni objektiv 2.8mm F2.0, - Vidni ugao 106° H, - Smart IC diode dometa cca. 25m, - Plastično kućište, - Dimenzije Ø85.0 mm × 77.1 mm, - Radna temperatura -40°C~+55°C, - Napajanje 12VDC ±30%/2.7W, - Pripadajuće dozne PFA12C 		
VND01051		<p><u>Dahua HAC-B2A51-U-0280B</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F2.0 fiksni objektiv, - Smart IC LE diode dometa cca. 30m, - Metalno kućište, - Dimenzije 150.0 mm × 69.7 mm × 70.0 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDC ±30%/3,7W, - Pripadajuće dozne PFA130-E, PFA134. 		




VND01053		<p><u>Dahua HAC-T2A51-U-0280B</u></p> <ul style="list-style-type: none"> - 5MP eyeball IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 106°H, - Smart IC LE diode dometa cca. 30m, - Metalno kućište, - Dimenzije $\Phi 94.0$ mm \times 77.9 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDc \pm30%/3.7W, - Pripadajuće dozne PFA13-A, PFB205W, PFA152-E, PFA106, PFB220C. 		
VND01022		<p><u>Dahua HAC-HFW1500C-0280B</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 111°H, - Smart IC LE diode dometa cca. 30m, - Plastično kućište, - Dimenzije 161.3mm \times 69.7mm \times 70.0mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDc \pm30%/3.7W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		
VND01012		<p><u>Dahua HAC-HFW1500T-A-0280B</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm fiksni objekti, - Smart IC diode dometa cca. 30m, - Integrisan mikrofoni, - Metalno kućište, - Dimenzije 174.5 mm \times 72.3 mm \times 70.6 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDc/3.2W, - Pripadajuće dozne PFA134, PFA152-E. 		




VND01025		<p><u>Dahua HAC-HFW1500TH-I8-0360B</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 3.6mm F1.6 fiksni objektiv, - Vidni ugao 92° H, - Smart IC diode dometa cca. 80m, - Metalno i plastično kućište, - Dimenzije 240.7 mm × 90.7 mm × 90.4 mm, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc ±30%/5.2W, - Pripadajuće dozne PFA130-E, PFA135, PFA152-E. 		
VND01082		<p><u>Dahua HAC-HFW1500RL-IL-A-0280B-S3</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 113.3° H, - Smart IC diode dometa cca. 30m, - Inkorporiran mikrofoni, - Starlight, Smart Light+ - Plastično kućište, - Dimenzije 161.6 mm × 70.0 mm × 69.7 mm, - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDc ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		
VND01082		<p><u>Dahua HAC-HFW1500RL-IL-T-0280B-S3</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 113.3° H, - Smart IC diode dometa cca. 30m, - Inkorporiran mikrofoni i zvučnik, dvosmerna komunikacija - Starlight, Smart Light+ - Plastično kućište, - Dimenzije 161.6 mm × 70.0 mm × 69.7 mm, - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDc ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		




VND01081		<p><u>Dahua HAC-HFW1500RM-IL-A-0280B-S3</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 113.3° H, - Smart IC diode dometa cca. 30m, - Inkorporiran mikrofon - Starlight, Smart Light+ - Metalno kućište, - Dimenzije 166.4 mm × 69.7 mm × 70.0 mm - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		
VND01086		<p><u>Dahua HAC-HFW1500TH-IL-A-0360B-S3</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 113.3° H, - Smart IC diode dometa cca. 80m, - Inkorporiran mikrofon - Starlight, Smart Light+ - Metalno i plastično kućište, - Dimenzije 240.7 mm × 90.7 mm × 90.4 mm - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA135, PFA152-E. 		
VND01027		<p><u>Dahua HAC-HFW1500TLM-IL-A-0360B-S3</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 113.3° H, - Smart IC i Bele le diode dometa cca. 40m, - Inkorporiran mikrofon - Starlight, Smart Light+ - Metalno i plastično kućište, - Dimenzije 198.4 mm × 80.2 mm × 76.2 mm - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		

VND01087		<p><u>Dahua HAC-HFW1549X-IL-A-PRO-0280B</u></p> <ul style="list-style-type: none"> - 5MP bullet kamera sa WizColor+AI-ISP tehnologijom, - 2.8mm F1.0 fiksni objektiv, - Vidni ugao 111.0° H, - Smart IC i Bele le diode dometa cca. 50m, - Inkorporiran mikrofoni i zvučnik, dvosmerna komunikacija - Starlight, Smart Light+ - Detekcija pokreta (kroz XVR) - 130db WDR, BLC, HLC, 3D DNR - Metalno i plastično kućište, - Dimenzije 186.5 mm × 75 mm × 82.2 mm - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA134, PFA151. 		
VND01087		<p><u>Dahua HAC-HFW1549X-A-PRO-0360B</u></p> <ul style="list-style-type: none"> - 5MP bullet kamera sa WizColor+AI-ISP tehnologijom, - 3,6mm F1.0 fiksni objektiv, - Vidni ugao 88,2° H, - Smart IC i Bele le diode dometa cca. 50m, - Inkorporiran mikrofoni i zvučnik, dvosmerna komunikacija - Starlight, Smart Light+ - Detekcija pokreta (kroz XVR) - 130db WDR, BLC, HLC, 3D DNR - Metalno i plastično kućište, - Dimenzije 186.5 mm × 75 mm × 82.2 mm - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA134, PFA151. 		

VND01085		<p><u>Dahua HAC-HFW1500TLM-IL-T-0280B-S3</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 113.3° H, - Smart IC i Bele le diode dometa cca. 40m, - Inkorporiran mikrofoni i zvučnik, dvosmerna komunikacija - Starlight, Smart Light+ - Metalno i plastično kućište, - Dimenzije 198.4 mm × 80.2 mm × 76.2 mm - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 		
VND01054		<p><u>Dahua HAC-HFW1500R-Z-IRE6-A-2712</u></p> <ul style="list-style-type: none"> - 5MP bullet kamera, - 2.7~12mm F1.6 motorizovani zum , - Podesivi vidni ugao 34°~107° H, - Smart IC LE diode dometa cca. 60m, - Integriran mikrofoni, - Starlight - Metalno kućište, - Dimenzije 209.9mm × 90.4mm × 90.4mm, - IP67 sertifikovana, - Radna temperatura -30°C~+60°C, - Napajanje 12VDC ±30% /9,8W, - Pripadajuće dozne PFA13G, PFA152-E, PFA130-E. 		
VND01056		<p><u>Dahua HAC-ME1509TH-A-PV-0360B</u></p> <ul style="list-style-type: none"> - 5MP Bullet kamera, - Fiksni objektiv 3.6 mm F1.0 , - Vidni ugao 89°H, - Bele I IC LE diode dometa cca. 40m, - Integriran mikrofoni, - Alarmni izlaz, - Alarm crveno-plavo svetlo sirena 110 db, - 120 dB true WDR, 3D NR, - Metalno i plasticno kućište, - Dimenzije 240.7mm × Ø90.7mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /10.5W, - Pripadajuće dozne PFA130-E, PFA152-E. 		

VND01008		<p><u>Dahua HAC-HDW1500CLQ-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 106°H, - Bele LE diode dometa cca. 20m, - Integrisan mikrofon, - Plastično kućište, - Dimenzije 97.1 mm × 93.8 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+55°C, - Napajanje 12VDc ±30% /4,5W, - Pripadajuće dozne PFA13G, PFA152-E, PFA205W-E. 		
VND01009		<p><u>Dahua HAC-HDW1500T-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 106°H, - Bele LE diode dometa cca. 40m, - Integrisan mikrofon, - Metalno kućište, - Dimenzije ϕ106.0 mm × 93.6 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc ±30% /4,5W, - Pripadajuće dozne PFA130, PFA152-E, PFA204W. 		
VND01036		<p><u>Dahua HAC-HDW1500T-Z-A-2712</u></p> <ul style="list-style-type: none"> - 5MP dom kamera, - Motorizovani objektiv 2.7~12mm F1.6 - Podesivi vidni ugao 34°~107°H, - Starlight - Smart IC LE diode dometa cca. 60m, - Integrisan mikrofon, - Metalno kućište, - Dimenzije ϕ122mm ×104.8mm - IP67 sertifikovana, - Radna temperatura -30°C~+60°C, - Napajanje 12VDc ±30% /6.6W - Pripadajuće dozne PFA130, PFA152-E, PFA137. 		

VND01040		<p><u>Dahua HAC-HDW1500TLMQ-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 106°H, - Bele I IC LE diode dometa cca. 20m, - Integrisan mikrofon, - Plastično i metalno kućište, - Dimenzije $\phi 109.9$ mm \times 88.1 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc $\pm 30\%$ /3.1W, - Pripadajuće dozne PFA13G, PFA152-E, PFA150, PFA205W-E. 		
VND01011		<p><u>Dahua HAC-HDW1500TRQ-0280B</u></p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 111°H, - IC LE diode dometa cca. 25m, - Starlight - Plastično kućište, - Dimenzije $\Phi 97.1$ mm \times 93.0 mm, - IP50 sertifikovana, - Radna temperatura -40°C~+50°C, - Napajanje 12VDc $\pm 30\%$ /3.0W, - Pripadajuće dozne PFA13G, PFA152-E, PFA205W-E. 		
VND01010		<p><u>Dahua HAC-HDW1500TLM-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 106°H, - Bele I IC LE diode dometa cca. 20m, - Integrisan mikrofon, - Metalno kućište, - Dimenzije $\phi 94.0$ mm \times 85.7 mm - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc $\pm 30\%$ /3.1W, - Pripadajuće dozne PFA13-A, PFA152-E, PFA205W-E. 		

VND01097		<p><u>Dahua HAC-HDW1500TQ-IL-T-0280B</u></p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 113.3°H, - Bele I IC LE diode dometa cca. 40m, - Integrisan mikrofon i zvučnik - dvosmerni audio, - Starlight, Smart Light+, Smart Area Lighting - Metalno i plastično kućište, - Dimenzije $\phi 109.9$ mm \times 105.9 mm - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC \pm30% /3.1W, - Pripadajuće dozne PFA13G, PFA150-V2, PFA205W-E. 		
VND01029		<p><u>Dahua HAC-ME1509TQ-PV-0280B</u></p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.0 , - Vidni ugao 111°H, - Bele I IC LE diode dometa cca. 40m, - Alarmni izlaz, - Alarm crveno-plavo svetlo, sirena 110 db, - Metalno i plasticno kućište, - Dimenzije $\Phi 109.9$ mm \times 100.9 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC \pm30% /10.5W, - Pripadajuće dozne PFA13G, PFA152-E, PFA205W-E. 		
VND01049		<p><u>HAC-HDBW1500E-0280B-S2</u></p> <ul style="list-style-type: none"> - 5MP antivandal dom kamera, - Objektiv 2.8mm, - Vidni ugao 111°H, - Dometa cca. 30m, - Metalno kućište, - Dimenzije $\phi 109.9$ mm \times 81.0 mm, - IP67, IK10 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC \pm30% /3,5W, - Pripadajuće dozne PFA136, PFB203W, PFA152-E. 		

<p>VND01088</p>		<p>Dahua HAC-HDW1549X-A-PRO-0360B</p> <ul style="list-style-type: none"> - 5MP dome kamera sa WizColor+AI-ISP tehnologijom, - 3,6mm F1.0 fiksni objektiv, - Vidni ugao 88,2° H, - Smart IC i Bele le diode dometa cca. 50m, - Inkorporiran mikrofon i zvučnik, dvosmerna komunikacija - Starlight, Smart Light+ - Detekcija pokreta (kroz XVR) - 130db WDR, BLC, HLC, 3D DNR - Metalno i plastično kućište, - Dimenzije 186.5 mm × 75 mm × 82.2 mm - IP67 sertifikovana - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/4.3W, - Pripadajuće dozne PFA130-E, PFA134, PFA151. 		
-----------------	---	--	--	--