











| Šifra | Slika | Opis | VP bez PDV-a | MP sa PDV-om |
|--|---|---|--------------|--------------|
| Dahua 2MPX ECO serija | | | | |
| <p>ECO SERIES</p> <p>VND02029</p> |  | <p><u>IPC-T1E20-A-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 115° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofon, - Plasticno kućište, - Dimenzije 103.2 mm × Φ109.9 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 2 VDC/PoE, potrošnja do 4,8W, ±30%, - Pripadajuće dozne PFA13-A, PFA130-E, PFB205W, PFA152-E, PFA151, PFA106 i PFB220C. | | |
| <p>ECO SERIES</p> <p>VND02053</p> |  | <p><u>IPC-B1E20-A-0360B</u></p> <ul style="list-style-type: none"> - 2MP bulit IC kamera, - 3.6mm F2.2 fiksni objektiv, - Vidni ugao 79° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofon, - Plasticno kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 2.8 W, ±30%, - Pripadajuće dozne PFA134, PFA130-E, PFA152-E. | | |




| | | | | |
|--|---|--|--|--|
| <p>ECO SERIES</p> <p>VND02089</p> |  | <p><u>IPC-B1E20-A-0280B</u></p> <ul style="list-style-type: none"> - 2MP bulit IC kamera, - 2.8mm F2.2 fiksni objektiv, - Vidni ugao 99° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofoni, - Plastico kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 2.8 W, ±30%, - Pripadajuće dozne PFA134, PFA130-E, PFA152-E. | | |
| <p>ECO SERIES</p> <p>VND02054</p> |  | <p><u>IPC-B1E29-A-IL-0360B</u></p> <ul style="list-style-type: none"> - 2MP bulit 2 Multi-core (IC + warm) - 3,6mm F1,6 fiksni objektiv, - Vidni ugao 87° H, - Domet dioda IC do 30 m, Led do 15 m - Integrisan mikrofoni, - Plastico kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE , potrošnja do 3.4 W (12 VDC); 4.2 W (PoE) - Pripadajuće dozne PFA134, PFA130-E, PFA152-E. | | |
| <p>ECO SERIES</p> <p>VND02105</p> |  | <p><u>IPC-T1E29-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dome 2 Multi-core (IC + warm) - 2,8mm F1,6 fiksni objektiv, - Vidni ugao 105° H, - Domet dioda IC do 30 m, Led do 15 m - Integrisan mikrofoni, - Plastico kućište, - Dimenzije 103.2 mm × Φ109.9 mm - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE , potrošnja do 3.4 W (12 VDC); 4.2 W (PoE) - Pripadajuće dozne PFA13G, PFB2203W, PFA152-E. | | |

Dahua IP 2MPX serija 1



| | | | | |
|-----------------|---|--|--|--|
| <p>VND02005</p> |  | <p><u>IPC-HDW1239V-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 104° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Metalno + Plastico kućište, - DWDR - Dimenzije 100.9 mm × Ø109.9 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do (H.265 + intelligence on+ WDR + illuminator intensity): 4.5 W (12 VDC); 5.6 W (PoE) - Pripadajuće dozne PFA13G, PFB205W, PFA152-E, PFA151, PFA106 i PFB220C. | | |
| <p>VND02008</p> |  | <p><u>IPC-HFW1239TL1-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP bullit, 4 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 104° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Metalno + Plastico kućište, - DWDR - Dimenzije 197.9 mm × 80.2 mm × 76.2 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do (H.265 + intelligence on+ WDR + illuminator intensity): 6.3 W (12 VDC); 7.8 W (PoE) - Pripadajuće dozne PFA134,,PFB205W, PFA152-E, | | |



| | | | | |
|-----------------|---|---|--|--|
| <p>VND02110</p> |  | <p><u>IPC-HDBW1239E1-A-IL-0280B-S6</u></p> <ul style="list-style-type: none"> - 2MP anti-vandal dom, 2 Multi-core (IC + warm) - 2.8mm fiksni objektiv, - Vidni ugao 95.5° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Masking (do 4 zone), Detekcija ljudi (SMD), Detekcija pokreta (do 4 zone), Detekcija zvuka - Potrebno napajanje 12VDC ili PoE - Metalno + Plastico kućište, - DWDR - Dimenzije IP67 i IK08 sertifikovana, - Radna temperatura -40°C~+60°C, - IP67 i IK08 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do (H.265 + intelligence on+ WDR + illuminator intensity): 4.5 W (12 VDC); 5.6 W (PoE) - Pripadajuće dozne PFA13G, PFB205W, PFA152-E, PFA151, PFA106 i PFB220C. | | |
| <p>VND02001</p> |  | <p><u>IPC-HDBW1230DE-SW-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 3 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Micro SD max. 256Gb - Metalno kućište, - DWDR - Dimenzije $\Phi 110.7$ mm \times 88.7 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 4.9 W (12 VDC) - Pripadajuće dozne PFA136, PFB203W, PFA152-E, PFA109 i PFB220C. | | |



| | | | | |
|----------|---|---|--|--|
| VND02007 |  | <p><u>IPC-HFW1230DS-SAW-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofoni, - Micro SD max. 256 Gb, - Metalno kućište, - DWDR - Dimenzije 166.2 mm × 70.0 mm × 128.6 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 4.1 W (12 VDC) - Pripadajuće dozne PFA134, PFA152-E | | |
| VND02047 |  | <p><u>IPC-HDW1230DT-SAW-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Micro SD max. 256 Gb, - Metalno + Plastično kućište, - DWDR - Dimenzije Ø109.9 mm × 102.2 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 6.1 W (12 VDC) - Pripadajuće dozne PFA13G, PFA134, PFA152-E, | | |
| VND02004 |  | <p><u>IPC-HFW1230DT-STW-0280</u></p> <ul style="list-style-type: none"> - 2MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofoni, - Micro SD max. 256 Gb, - Plastično kućište, metalni nosac, - DWDR - Dimenzije 166.2 mm × 70.0 mm × 128.6 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2,2 W (12 VDC), potrošnja do 6.21 W (12 VDC) - Pripadajuće dozne PFA134,PFA152-E | | |



| | | | | |
|----------|---|--|--|--|
| VND02002 |  | <p><u>IPC-HDBW1230E-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 3 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 104° H, - Smart IC diode dometa cca. 30m, - Metalno kućište, - DWDR - Dimenzije $\Phi 109.9\text{mm} \times 81\text{mm}$, - Radna temperatura $-30^{\circ}\text{C}\sim+60^{\circ}\text{C}$, - IP67 , IK10 sertifikovana, - Napajanje DC12V, PoE , potrošnja do <5W - Pripadajuće dozne PFA136,PFB203W, PFA152-E | | |
| VND02086 |  | <p><u>IPC-HDW1230T-ZS-2812</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 IC kamera - 2.8 mm–12 mm F1.7 moto-zoom, - Vidni ugao 101°–33.5° H, - Smart IC diode dometa cca. 40m, - Micro SD max. 256 GB, - Metalno kuciste, - DWDR - Dimenzije 108.3 mm \times $\Phi 122$ mm - Radna temperatura $-30^{\circ}\text{C}\sim+60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 12V DC/PoE , potrošnja do 3.9 W (12 V DC); 5 W (PoE) - Pripadajuće dozne: PFA130-E,PFA152-E, PFB205W | | |
| VND02012 |  | <p><u>IPC-HFW1230T-ZS-2812-S5</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 IC kamera - 2.8 mm–12 mm F1.7 moto-zoom, - Vidni ugao 101°–33.5° H, - Smart IC diode dometa cca. 50m, - Integrisan mikrofon, - Micro SD max. 256 GB, - Metalno kuciste, - DWDR - Dimenzije 244.1 mm \times $\Phi 90.4$ mm - Radna temperatura $-40^{\circ}\text{C}\sim+60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 12V DC/PoE , potrošnja do 4.3 W (12V DC); 5.5 W (PoE) - Pripadajuće dozne: PFA130-E,PFA152-E | | |



Dahua 2MPX serija 2

| | | | | |
|-----------------|---|--|--|--|
| <p>VND02048</p> |  | <p><u>IPC-HDW2249TM-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 107° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikroskop, - Micro SD max. 256Gb - Metalno kućište, plastican prsten, - DWDR - Dimenzije 99.1 mm × Ø121.9 mm , - Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V, PoE , potrošnja do 3.8 W (12 VDC); 4.4 W (PoE) - Pripadajuće dozne PFA130-E, PFB203W, PFA152-E, PFA109 i PFB220C | | |
| <p>VND02011</p> |  | <p><u>IPC-HFW2249S-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 107° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikroskop, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 166.2 mm × 70 mm × 70mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 3.8 W (12 VDC); 4.4 W (PoE) - Pripadajuće dozne PFA130-E, PFA134, PFA152-E | | |



| | | | | |
|----------|---|---|--|--|
| VND02094 |  | <p><u>IPC-HFW2249T-AS-IL-0360B</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 (IR LED); 2 (Warm light) - 3.6mm F1.6 fiksni objektiv, - Vidni ugao 84° H, - Domet do 60 m (IR), i 50 m (Warm light), - Integrisan mikroskop, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 238.5 mm × 90.7 mm × 90.7 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 5.8 W (12 VDC); 6.9 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E | | |
| VND02057 |  | <p><u>IPC-HDBW2249E-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 3 (IC LED); 4 (Warm light) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 105° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikroskop, - Micro SD max. 256 GB - Metalno kućište, plastican prsten, - DWDR - Dimenzije 81.0 mm × Φ109.9 mm, - Radna temperatura -30°C~+60°C, - IP67, IK10, sertifikovana, - Napajanje DC12V, PoE , potrošnja do 6.2 W (12 VDC), 7.5 W (PoE) - Pripadajuće dozne PFA136, PFB203W, PFA152-E, PFA109 i PFB220C | | |

| | | | | |
|----------|---|---|--------|--------|
| VND02058 |  | <p><u>IPC-HDW2241T-ZS-27135</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 IC diode - 2.7 mm–13.5 mm F1.5 objektiv Moto-zoom, - Vidni ugao 108°–30° H, - Smart IC LE diode dometa cca. 40m, - Integrisan mikrofoni, - Micro SD max. 256 GB, - Metalno kućište, - DWDR - Dimenzije 108.3 mm × Φ122 mm, - Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V, PoE , potrošnja do 5.7 W (12 VDC); 6 W (PoE) - Pripadajuće dozne PFA130-E, PFB205W-E, PFA152-E, PFA106 i PFB220C | 300.00 | 360.00 |
| VND02075 |  | <p><u>IPC-HFW2241T-ZAS-27135</u></p> <ul style="list-style-type: none"> - 2MP dom, 4 (IR LED) - 2.7 mm–13.5 mm F1.5 objektiv Moto-zoom, - Vidni ugao 108°–30° H, - Smart IC LE diode dometa cca. 60m, - Integrisan mikrofoni, - Micro SD max. 256 GB, - Metalno kućište, - DWDR - Dimenzije 238.5 mm × 90.7 mm × 90.7 mm , - Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V, PoE , potrošnja do 8.6 W (12 VDC); 9.9 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E, | | |

| | | | | |
|-----------------|---|---|--|--|
| <p>VND02095</p> |  | <p><u>IPC-HFW2249T-ZAS-IL-27135</u></p> <ul style="list-style-type: none"> - 2MP dom, 4 (Multi-core (IR + warm light)) - 2.7 mm–13.5 mm F1.5 objektiv Moto-zoom, - Vidni ugao 109°–30° H, - Smart IC LE diode dometa cca. 60m, - Integrisan mikrofon, - Micro SD max. 256 GB, - Metalno kućište, - DWDR - Dimenzije 238.5 mm × 90.7 mm × 90.7 mm, - Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V, PoE , potrošnja do 10.2 W (12 VDC), 12.7 W (PoE) (H.265 + intelligence on+ WDR + warm light intensity) - Pripadajuće dozne PFA130-E, PFA135, PFA152-E, PFA151 | | |
| <p>VND02096</p> |  | <p><u>IPC-HFW2249M-S-B-PRO-0280</u></p> <ul style="list-style-type: none"> - 2MP dom, 4 (Warm light) - 3.6mm F1.0 fiksni objektiv, - Vidni ugao 81° H, - Smart IC LE diode dometa cca. 50m, - Integrisan mikrofon, - Micro SD max. 256 GB, - Metalno + polasticno kućište, - DWDR - Dimenzije 201.0 mm × 103.8 mm × 97.8 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 5.3 W (12 VDC); 6.3 W (PoE) (H.265+ intelligence on + WDR + illuminator intensity) - Pripadajuće dozne PFA121, PFB121W, PFA152-E, PFA150 | | |

| | | | | |
|----------|---|--|--|--|
| VND02098 |  | <p><u>IPC-HFW2249TL-S-PRO-0280</u></p> <ul style="list-style-type: none"> - 2MP dom, 4 (Warm light) - 2.8mm F1.0 fiksni objektiv, - Vidni ugao 101°H, - Smart IC LE diode dometa cca. 50m, - Integrisan mikrofon, - Micro SD max. 256 GB, - Metalno kućište, - DWDR - Dimenzije 197.9 mm × 80.2 mm × 76.2 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 5.3 W (12 VDC); 6.3 W (PoE) (H.265+ intelligence on + WDR + illuminator intensity) - Pripadajuće dozne PFA130-E, PFA134, PFA151 | | |
| VND02098 |  | <p><u>IPC-HDW2249T-S-LED-0280B-PRO</u></p> <ul style="list-style-type: none"> - 2MP dom, 4 (Warm light) - 2.8mm F1.0 fiksni objektiv, - Vidni ugao 101°H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - WizColor+AI-ISP tehnologija - Micro SD max. 256 GB, - Metalno kućište, - DWDR - Dimenzije 109.5 mm × Φ109.9 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDC ili PoE (802.3af), potrošnja do 5.7W - Pripadajuće dozne PFA13G, PFB2203W, PFA152-E | | |

Dahua 3MPX serija 1

| | | | | |
|-----------------|---|---|---------------|---------------|
| <p>VND02090</p> |  | <p><u>IPC-HDW1339DA-SAW-IL-0280</u></p> <ul style="list-style-type: none"> - 3MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 103° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofoni, - Micro SD max. 256 GB - Metalno+plasticno kućište, - DWDR - Dimenzije 102.2 mm × Φ109.9 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC, potrošnja do 4.9 W (12 VDC) (H.265 + warm light on) - Pripadajuće dozne PFA130-E, PFA13G, PFA152-E, PFB205W-E, PFB220C+PFA109 | <p>114.00</p> | <p>136.80</p> |
| <p>VND02091</p> |  | <p><u>IPC-HFW1339DTK1-SAW-IL-0280</u></p> <ul style="list-style-type: none"> - 3MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 103° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofoni, - Micro SD max. 256 GB - Metalno+plasticno kućište, - DWDR - Dimenzije 172.4 mm × 83.3 mm × 75.0 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC, potrošnja do 4.1 W (12 VDC) - Pripadajuće dozne PFA130-E, PFA134, PFA152-E | <p>112.00</p> | <p>134.40</p> |