











Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
Dahua ECO serija				
<p>ECO SERIES</p> <p>VND02016</p>		<p><u>IPC-T1E40-A-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom IC kamera, - 2.8mm F2.2 fiksni objektiv, - Vidni ugao H: 90°, - Smart IC diode dometa cca. 30m, - Integrisan mikroskop, - Plastično kućište, - Dimenzije 103.2 mm × Φ109.9 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 3.0 W (12 VDC); 4.2 W (PoE) - Pripadajuće dozne PFA13-G, PFA130-E, PFB205W, PFA152-E, PFA151, PFA109 i PFB220C. 		
<p>ECO SERIES</p> <p>VND02030</p>		<p><u>IPC-B1E40-A-0360B</u></p> <ul style="list-style-type: none"> - 4MP bulit IC kamera, - 3.6mm F2.2 fiksni objektiv, - Vidni ugao 76°H, - Smart IC diode dometa cca. 30m, - Integrisan mikroskop, - Plastično kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 3.0 W (12 VDC); 4.2 W (PoE) - Pripadajuće dozne PFA134, PFA130-E, PFA152-E. 		

<p>ECO SERIES</p> <p>VND02055</p>		<p><u>IPC-B1E49-A-IL-0360B</u></p> <ul style="list-style-type: none"> - 4MP bulit 2 Multi-core (IC + warm) - 3,6mm F1,6 fiksni objektiv, - Vidni ugao 78° H, - Domet dioda IC do 30 m, Led do 15 m - Integrisan mikrofon, - Plasticno kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE , potrošnja do 3.3 W (12 VDC); 4.25 W (PoE) - Pripadajuće dozne PFA134, PFA130-E, PFA152-E. 		
<p>ECO SERIES</p> <p>VND02104</p>		<p><u>IPC-T1E49-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom 2 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 94° H, - Domet dioda IC do 30 m, Led do 30 m - Integrisan mikrofon, - Plasticno kućište, - Dimenzije 103.2 mm × Φ109.9 mm - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE , potrošnja do 3.3 W (12 VDC); 4.25 W (PoE) - Pripadajuće dozne PFA13G, PFA152-E. 		
Dahua serija 1				
<p>VND02052</p>		<p><u>IPC-HDW1439V-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 94° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Metalno + Plasticno kućište, - DWDR - Dimenzije 100.9 mm × Φ109.9 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do: 4.6 W (12 VDC); 5.7 W (PoE) - Pripadajuće dozne PFA13G,,PFB205W, PFA152-E, PFA151, PFA106 i PFB220C. 		



VND02025		<p><u>IPC-HDW1439V-A-IL-0280B BLACK</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 94° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofoni, - Metalno + Plastično kućište, - DWDR - Dimenzije 100.9 mm × Φ109.9 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do: 4.6 W (12 VDC); 5.7 W (PoE) - Pripadajuće dozne PFA13G,,PFB205W, PFA152-E, PFA151, PFA106 i PFB220C. 		
VND02013		<p><u>IPC-HFW1439TL1-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP bullit, 4 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 94° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofoni, - Metalno + Plastično kućište, - DWDR - Dimenzije 197.9 mm × 80.2 mm × 76.2 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do: 6.4 W (12 VDC); 7.7 W (PoE) - Pripadajuće dozne PFA134, PFB205W, PFA152-E. 		
VND02126		<p><u>IPC-HDBW1439E1-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP anti-vandal dom kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 95.5° H, - Smart IC diode dometa cca. 30m, - Micro SD max. 256 GB - Metalno i plastično kućište, - Integrisan mikrofoni, - DWDR - Dimenzije 81.0 mm × Φ109.9 mm , - Radna temperatura -40°C~+60°C, - IP67, IK10 sertifikovana, - Napajanje 12 VDC, potrošnja do 4.9 W (12 VDC) - Pripadajuće dozne PFA136,PFB203W, 		


VND02076		<p><u>IPC-HFW1439TL1-A-IL-0280B BLACK</u></p> <ul style="list-style-type: none"> - 4MP bullit, 4 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 94° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Metalno + Plastično kućište, - DWDR - Dimenzije 197.9 mm × 80.2 mm × 76.2 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do: 6.4 W (12 VDC); 7.7 W (PoE) - Pripadajuće dozne PFA134, PFB205W, PFA152-E. 		
VND02003		<p><u>IPC-HDBW1430DE-SW-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom anti-vandal, 3 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 90° H, - Smart IC diode dometa cca. 30m, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije Φ110.7 mm × 88.7 mm , - Radna temperatura -40°C~+60°C, - IP67, IK10 sertifikovana, - Napajanje 12 VDC, potrošnja do 4.9 W (12 VDC) - Pripadajuće dozne PFA136,PFB203W, PFA152-E, PFA109 i PFB220C. 		
VND02009		<p><u>IPC-HFW1430DS-SAW-0280B</u></p> <ul style="list-style-type: none"> - 4MP bullit, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 166.2 mm × 70.0 mm × 128.6 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 4.1 W (12 VDC) - Pripadajuće dozne PFA134,PFA152-E. 		


VND02051		<p><u>IPC-HDW1430DT-SAW-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 90° H, - Smart IC diode dometa cca. 30m, - Micro SD max 256GB - Metalno + Plastico kućište, - DWDR - Dimenzije Ø109.9 mm × 102.2 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 4.2 W (12 VDC) - Pripadajuće dozne PFA13G, PFA130-E, PFA152-E, PFA109+PFB220C 		
VND02009		<p><u>IPC-HFW1430DS-SAW-0280</u></p> <ul style="list-style-type: none"> - 4MP bullit, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 90° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofoni, - Micro SD max.256 GB - Plastico kućište, metalni nosac, - DWDR - Dimenzije 180 mm × 83.3 mm × 114.8 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC, potrošnja do 6.1 W (12 VDC) - Pripadajuće dozne PFA134,PFA152-E 		
VND02056		<p><u>IPC-HDW1431S-S-0280B-S4</u></p> <ul style="list-style-type: none"> - 4MP dom, 12 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 104° H, - Smart IC diode dometa cca. 30m, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije Ø108mm×84.9mm(- Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V, PoE, potrošnja do 5.5W - Pripadajuće dozne PFA130-E,PFA152-E, PFB203W 		



VND02044		<p><u>IPC-HDW1431T-ZS-2812-S4</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 IC kamera - 2.8 mm–12 mm F1.7 moto-zoom, - Vidni ugao 98°–31° H, - Smart IC diode dometa cca. 50m, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 108.3 mm × Φ122 mm , - Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.9W - Pripadajuće dozne PFA133-E, PFB203W, PFA152-E, PFA106+PFB220C 		
VND02040		<p><u>IPC-HFW1431T-ZS-2812-S4</u></p> <ul style="list-style-type: none"> - 4MP bullit, 2 IC kamera - 2.8 mm–12 mm F1.7 moto-zoom, - Vidni ugao 98° - 31° H, - Smart IC diode dometa cca. 50m, - Integrisan mikrofon, - Micro SD max. 256 GB, - Metalno kuciste, - DWDR - Dimenzije 244.1mm × Φ90.4 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12V DC/PoE, potrošnja do 7.4W - Pripadajuće dozne: PFA130-E, PFA152-E 		
Dahua serija 2				
VND02039		<p><u>IPC-HDW2449TM-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 95° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Micro SD max. 256 GB, - Metalno kućište, plastican prsten, - DWDR - Dimenzije 99.1 mm × Φ121.9 mm, - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 4.4 W (12 VDC); 5.2 W (PoE) - Pripadajuće dozne PFA130-E, PFB203W, PFA152-E, PFA109 i PFB220C 		



VND02062		<p><u>IPC-HDW2449TM-S-IL-0280B BLACK</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 95° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Micro SD max. 256 GB, - Metalno kućište, plastican prsten, - DWDR - Dimenzije 99.1 mm × Φ121.9 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 4.4 W (12 VDC); 5.2 W (PoE) - Pripadajuće dozne PFA130-E, PFB203W, PFA152-E, PFA109 i PFB220C 		
VND02125		<p><u>IPC-HDBW2449E-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom anti-vandal - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 101° H, - Smart IC LE i Bele diode dometa cca. 30m, - Integrisan mikrofon, - WDR 120dB; 3D DNR; ROI - Micro SD max. 256 GB, - Metalno kućište, plastican prsten, - DWDR - Dimenzije 99.1 mm × Φ121.9 mm, - Radna temperatura -30°C~+60°C, - IP67 i IK10 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.6 W (12 VDC); 5.2 W (PoE) 		
VND02034		<p><u>IPC-HFW2449S-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP bullit, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 95° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 166.2 mm × 70 mm × 70mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 4.4 W (12 VDC); 5.2 W (PoE) - Pripadajuće dozne PFA130-E, PFA134, PFA152-E 		


VND02019		<p><u>IPC-HFW2449T-AS-IL-0360B</u></p> <ul style="list-style-type: none"> - 4MP bullit, 2 (IC LED); 2 (Warm light) - 3,6 mm F1.6 fiksni objektiv, - Vidni ugao 84° H, - Smart IC LE diode dometa cca. 60m, cca 50 m (Warm light) - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 238.5 mm × 90.7 mm × 90.7 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.1 W (12 VDC); 7.2 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E. 		
VND02066		<p><u>IPC-HFW2449T-AS-IL-0360B BLACK</u></p> <ul style="list-style-type: none"> - 4MP bullit, 2 (IC LED); 2 (Warm light) - 3,6 mm F1.6 fiksni objektiv, - Vidni ugao 84° H, - Smart IC LE diode dometa cca. 60m, cca 50 m (Warm light) - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 238.5 mm × 90.7 mm × 90.7 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.1 W (12 VDC); 7.2 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E. 		

<p>VND02067</p>		<p><u>IPC-HFW2449TL-S-LED-0280B-PRO</u></p> <ul style="list-style-type: none"> - 4MP bulit kamera WizColor+AI-ISP tehnologija - 2.8 mm F1.6 fiksni objektiv, - Vidni ugao 105° H, - Pametne bele LE diode dometa cca. 50m - AI Analitika - detekcija prelaska definisane linije i ulaska/izlaska u definisani region - SMD+; Detekcija pokreta (do 4 zone) - Integrisan mikrofon, - BLC /HLC /WDR 120dB; 3D DNR, LDC; RO - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 197.9 mm × 80.2 mm × 76.2 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.7 W (12 VDC); 7.2 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E. 		
-----------------	---	--	--	--

<p>VND02067</p>		<p><u>IPC-HFW2449M-S-B-PRO</u></p> <ul style="list-style-type: none"> - 4MP bulit kamera WizColor+AI-ISP tehnologija - 2.8 mm F1.6 fiksni objektiv, - Vidni ugao 105° H, - Pametne bele LE diode dometa cca. 50m - AI Analitika - detekcija prelaska definisane linije i ulaska/izlaska u definisani region - SMD+; Detekcija pokreta (do 4 zone) - Integrisan mikrofoni, - BLC /HLC /WDR 120dB; 3D DNR, LDC; RO - Micro SD max. 256 GB - Metalno I plastično kućište - DWDR - Dimenzije 201.0 mm × 103.8 mm × 97.8 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.7 W (12 VDC); 7.2 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E. 		
-----------------	---	---	--	--

VND02064		<p><u>IPC-HDW2449T-S-LED-0280B-PRO</u></p> <ul style="list-style-type: none"> - 4MP dom kamera WizColor+AI-ISP tehnologija - 2.8 mm F1.6 fiksni objektiv, - Vidni ugao 105° H, - Pametne bele LE diode dometa cca. 30m - AI Analitika - detekcija prelaska definisane linije i ulaska/izlaska u definisani region - SMD+; Detekcija pokreta (do 4 zone) - Integrisan mikrofoni, - BLC /HLC /WDR 120dB; 3D DNR, LDC; RO - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 109.5 mm × Φ109.9 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.7 W (12 VDC); - Pripadajuće dozne PFA13G, PFA152-E, PFB2203W. 		
		<p><u>IPC-HDW2441T-ZS-27135</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 (IC LED); - 2.7 mm–13.5 mm F1.5 moto zoom objektiv, - Vidni ugao 104°–29° H, - Smart IC LE diode dometa cca. 40m, - Integrisan mikrofoni, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 108.3 mm × Φ122 mm, - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.1 W (12 VDC); 7.3 W (PoE) - Pripadajuće dozne PFA130, PFB205W, PFA152-E, PFA106 i PFB220C. 		

		<p><u>IPC-HDBW2449R-ZAS</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 (IC LED); 4 (Warm light) - 2.7 mm–13.5 mm F1.5 motozoom objektiv, - Vidni ugao 104°–29° H, - Smart IC LE diode dometa cca. 40m, - Integrisan mikrofoni, - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 93.4 mm × Φ122 mm, - Radna temperatura -30°C~+60°C, - IP67 , IK10, sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.5 W (12 VDC); 7.7 W (PoE) - Pripadajuće dozne PFA137, PFB203W, PFA152-E, PFA109 i PFB220C. 		
VND02037		<p><u>IPC-HDW2449T-ZS-IL-27135</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.7 mm–13.5 mm F1.5 moto zoom objektiv, - Vidni ugao 97°–28° H, - Smart IC LE diode dometa cca. 40m, - Integrisan mikrofoni, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 108.3 mm × Φ122.0 mm, - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 7.8 W (12 VDC), 9.3 W (PoE) - Pripadajuće dozne PFA130, PFB205W, PFA152-E, PFA106 i PFB220C. 		

<p>VND02070</p>		<p>IPC-HFW3441T- S-P-0210B</p> <ul style="list-style-type: none"> - 4MP bullet, AI IP 180°, Starlight - 2,1 mm fiksni objektiv, - Vidni ugao 180° H, - Smart IC LE diode dometa cca. 20m, - WDR 120dB; BLC; HLC; 3D DNR; - Detekcija pokreta (do 4 zone); AI Analitika - detekcija prelaska definisane linije i ulaska/izlaska u definisani region - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 249.3 mm × 90.7 mm × 90.4 mm , - Radna temperatura -40°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.5 W (12 VDC); - Pripadajuće dozne PFA130-E, PFA135 PFA152-E. 		
-----------------	---	--	--	--