



Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
Dahua 5MPX WIFI				
VND02093		<u>IPC-HDW1539DA-SAW-IL</u> - 5MP dom, 1 (IR LED); 1 (Warm light) - 2,8mm F1.6 fiksni objektiv, - Vidni ugao 108°H, - Diode dometa cca. 30m, - Integriran mikrofoni, - Micro SD max. 256 GB - Metalno + Plastično kućište, - Dimenzije 102.2 mm × Ø109.9 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC, potrošnja do 5.1 W(12 VDC); - Pripadajuće dozne PFA13G, PFB205W, PFA152-E.		
VND02092		<u>IPC-HFW1539DTK1-SAW-IL</u> - 5MP bulit 1 (Multi-core (IR + warm) light) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 104°H, - Diode dometa cca. 30m, - Integriran mikrofoni, - Micro SD max. 256 GB - Metalno + Plastično kućište, - Dimenzije 172.4 mm × 83.3 mm × 75.0 mm, - Radna temperatura -30°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC, potrošnja do 4.3 W (12 VDC); - Pripadajuće dozne PFA134, PFA130-E, PFA152-E.		

Dahua serija 2				
VND02035		<u>IPC-HDW2541TM-S</u> - 5MP dom, 1 (IR LED) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 111° H, - Diode dometa cca. 30m, - Mikrofon: nema, - Metalno kućište, - DWDR - Dimenzije 99.1 mm × Φ121.9 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do: 4.1 W (12 VDC); 5.0 W (PoE) - Pripadajuće dozne PFA13G,PFB205W, PFA152-E, PFB220C.		
VND02033		<u>IPC-HFW2541S-S</u> - 5MP bullit, 1 (IR LED) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 111° H, - Diode dometa cca. 30m, - Integrisan mikrofon, - Metalno kućište, - DWDR - Dimenzije 166.2 mm × 70 mm × 70 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do: 4.1 W (12 VDC); 5.0 W (PoE) - Pripadajuće dozne PFA134, PFA130-E,PFA152-E.		
Dahua serija 3				
VND02083		<u>IPC-HDW3549H-AS-PV TiOC</u> - 5MP dom, 1 (IR LED); 1 (Warm light) - 2.8mm F1.0 fiksni objektiv, - Vidni ugao 97° H, - Diode dometa cca. 30m, - Micro SD max. 512 GB - Metalno kućište, - DWDR - Dimenzije Φ122.0 mm × 110.9 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/POE, potrošnja do 8.3 W (12 VDC); 8.8 W (PoE) - Pripadajuće dozne PFA137,PFA130-E, PFA152-E,		

VND02084		<u>IPC-HDW3541TM-AS</u> - 5MP dom, 2 (IR LED) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 98° H, - Diode dometa cca. 30m, - Metalno kućište, - DWDR - Dimenzije $\Phi 99.1 \text{ mm} \times \Phi 121.9 \text{ mm}$, - Radna temperatura $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 12 VDC/POE, potrošnja $< 8.1\text{W}$ - Pripadajuće dozne PFA130-E, PFA152-E.		
VND02085		<u>IPC-HDW3541T-ZS</u> - 5MP dom, 2 (IR LED) - 2.7 mm–13.5 mm, F1,5 moto-zum objektiv, - Vidni ugao 99°–28°H, - Diode dometa cca. 40m, - Metalno kućište, - DWDR - Dimenzije $108.3 \text{ mm} \times \Phi 122 \text{ mm}$, - Radna temperatura $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 12 VDC, potrošnja do 8.9 W (12 VDC); 10.2 W (PoE) - Pripadajuće dozne PFA137, PFA130-E, PFA152-E, PFB220C		
Dahua Serija 5				
VND02059		<u>IPC-HDW5541TM-ASE</u> - 5MP dom, 2 (IR LED) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 111° H, - Diode dometa cca. 50m, - Integriran mikrofoni, - Plastično kućište, metalni nosac, - DWDR - Dimenzije $99.1 \text{ mm} \times \Phi 121.9 \text{ mm}$ - Radna temperatura $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 12 VDC/POE, potrošnja do 6.2 W (12 VDC); 8.3 W (PoE) - Pripadajuće dozne PFA130-E, PFB205W, PFA152-E		

VND02018		<u>IPC-HFW5541T-ASE</u> - 5MP dom, 4 (IR LED) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 111° H, - Diode dometa cca. 80m, - Integrisan mikrofoni, - Plastično kućište, metalni nosac, - DWDR - Dimenzije 244.1 mm × 79.0 mm × 75.9 mm - Radna temperatura -40°C~+60°C, - IP67 , IK10 sertifikovana, - Napajanje 12 VDC/POE, potrošnja do 6.2 W (12 VDC); 8.3 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E		
Dahua 6MPX Serija 1				
VND02006		<u>IPC-HDW1639T-A-IL</u> - 6MP dom,1 (Multi-core (IR + warm) light) - 2.8 mm F1.6 fixni objektiv, - Vidni ugao 110° H, - Diode dometa cca. 30m, - Metalno kućište, - DWDR - Dimenzije 85.6 mm × Ø94.0 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V/PoE, potrošnja do 4 W (12 VDC); 5.3 W (PoE) - Pripadajuće dozne PFA13A-E, PFB204W, PFA152-E, PFA106+PFB220C		

VND02063		<u>IPC-HFW1639TC-A-IL</u> - 6MP bullet, 1 (Multi-core (IR + warm) light) - 2.8 mm F1.6 fixni objektiv, - Vidni ugao 110° H, - Diode dometa cca. 30m, - Integriran mikrofoni, - Metalno kućište, - DWDR - Dimenzije 173.3 mm × 70.0 mm × 70.0 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12V DC/PoE, potrošnja do 4 W (12 VDC), 5.3 W (PoE) - Pripadajuće dozne: PFA130-E, PFA134, PFA152-E		
Dahua 6MPX Serija 2				
VND02102		<u>IPC-HDBW2649E-S-IL-0280B</u> - 6MP dom, 3 (IR LED); 4 (Warm light) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 112° H, - Diode dometa cca. 30m, - Integriran mikrofoni, - Metalno kućište, - DWDR - Dimenzije 81.0 mm × Φ109.9 mm, - Radna temperatura -40°C~+60°C, - IP67 , IK10, sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.8 W (12 VDC); 8.2 W (PoE) - Pripadajuće dozne PFA136, PFB203W, PFA152-E, PFA109 i PFB220C		

VND02133		<u>IPC-HDW2649T-S-PRO</u> - 6MP dom, 2 (Warm light) - 2.8mm F1.0 fiksni objektiv, - Vidni ugao 92° H, - Diode dometa cca. 30m, - Integriran mikrofon, - Metalno jezgro, plastican cover, - DWDR - Dimenzije 9109.5 mm × Ø109.9 mm , - Radna temperatura -40°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 5.6 W (12 VDC); 6.4 W (PoE) - Pripadajuće dozne PFA130-E, PFA13G, PFB2203W, PFA152-E, PFA109 i PFB220C		
VND02136		<u>IPC-HFW2649TL-S-LED-PRO</u> - 6MP dom, 4 (Warm light) - 2.8mm F1.0 fiksni objektiv, - Vidni ugao 92° H, - Diode dometa cca. 30m, - Integriran mikrofon, - Metalno kućište, - DWDR - Dimenzije 197.9 mm × 80.2 mm × 76.2 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 6.1 W (12 VDC); 7.4 W (PoE) - Pripadajuće dozne PFA130-E, PFA134, PFA152-E		
VND02135		<u>IPC-HFW2649S-S-IL-0280B</u> - 6MP dom, 1 (IR LED); 1 (Warm light) - 2.8 mm F1.6 fiksni objektiv, - Vidni ugao 112° H, - Diode dometa cca. 30m, - Integriran mikrofon, - Metalno kućište - DWDR - Dimenzije 169.8 mm × 70 mm × 70 mm - Radna temperatura -40°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 4.4 W (12 VDC); 5.4 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E.		

VND02128		<u>IPC-HFW2649T-ZAS-IL</u> - 4MP dom, 4 (Multi-core (IR + warm) light) - 2,7-13,5mm F1.5 fiksni objektiv, - Vidni ugao 114°–32° H, - Diode dometa cca. 60m, - Integrisan mikrofoni, - Metalno kućište - DWDR - Dimenzije 238.5 mm × 90.7 mm × 90.7 mm , - Radna temperatura -30°C~+60°C, - IP67 , IK10, sertifikovana, - Napajanje DC12V, PoE, potrošnja do 10.2 W (12 VDC), 12.7 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E.		
Dahua 6MPX Serija 3				
VND02065		<u>IPC-HDW3649H-AS-PV-PRO</u> - 6MP dom, 2 (Multi-core (IR + warm) light) - 2.8mm F1.0 fixni objektiv, - Vidni ugao 109°H, - Diode dometa cca. 30m, - Integrisan mikrofoni, - Metalno kućište, - DWDR - Dimenzije Φ122.0 mm × 116.1 mm , - Radna temperatura -40°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 8.2 W (12 VDC); 10 W (PoE) - Pripadajuće dozne PFA137, PFB205W, PFA152-E, PFA109 i PFB220C.		

VND02140		<u>IPC-HDW1839T-A-IL</u> - 8MP dom, 3 (IR LED); 4 (Warm light) - 2.8mm F1.6 FIXNI objektiv, - Vidni ugao 110° H, - Diode dometa cca. 30m, - Integrisan mikrofoni, - Metalno + plasticno kućište, - DWDR - Dimenzije 81.0 mm × Φ109.9 mm , - Radna temperatura -40°C~ +60°C, - IP67 , IK08, sertifikovana, - Napajanje DC12V, PoE, potrošnja do 7 W (12 VDC); 8.3 W (PoE) - Pripadajuće dozne PFA136, PFB2203W, PFA156,		
VND02100		<u>IPC-HFW1839TC-A-IL</u> - 8MP dom, 1 (Multi-core (IR + warm) light) - 2.8mm F1.6 fixni objektiv, - Vidni ugao 110° H, - Diode dometa cca. 30m, - Integrisan mikrofoni, - Metalno kućište, - DWDR - Dimenzije 173.3 mm × 70.0 mm × 70.0 mm, - Radna temperatura -40°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 4.5 W (12 VDC), 5.8 W (PoE) - Pripadajuće dozne PFA130, PFA134, PFA152-E,		