











Tiandy



Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
Tiandy IPC 2MP				
VNT01001		<p><u>TC-C321N Spec:I3/E/Y/2.8mm V2.0</u></p> <ul style="list-style-type: none"> - 2MP bulit IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102.8°(H); 57.6°(V), - Smart IC diode dometa 30m, - Integrisan mikrofoni, - Metal + plastika kućište, - Dimenzije 164 x 73 x73 mm, - Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje PoE, potrošnja do 6W, - DWDR, BLC, HLC, AGC, 3D DNR, MD, - WEB Browser, Easy7 VMS - Dozne PFA134, PFA130 	41.00	49.20
VNT01002		<p><u>TC-C320N Spec:I3/E/Y/2.8mm</u></p> <ul style="list-style-type: none"> - 2MP dom IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 102.8°(H); 57.6°(V), - Smart IC diode dometa 30m, - Integrisan mikrofoni, - Metal + plastika kućište, - Dimenzije 117 x 117 x 96 mm, - Radna temperatura -30°C~+60°C, - Napajanje PoE, potrošnja do 6W, - DWDR, BLC, HLC, AGC, 3D DNR, MD, - WEB Browser, Easy7 VMS - Dozne BA-01, PFA1230R, PFA12C 	41.00	49.20



Tiandy IPC 4MP				
VNT01004		<p><u>TC-C34XN Spec: I3W/E/Y/2.8mm/V5.0</u></p> <ul style="list-style-type: none"> - 4MP dom IC + WL kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 100.1°(H); 54.3°(V), - Smart IR diode dometa 30m, WL diode dometa 15m, - Integrisan mikrofon, - Metal + plastika kućište, - Dimenzije 117 x 117 x 96 mm, - Radna temperatura -30°C~+60°C, - Napajanje PoE, DC 12V ±25%, potrošnja do 7W, - WDR, BLC, HLC, AGC, 3D DNR, MD, Tripwire, Perimeter, - WEB Browser, Easy7 VMS, EasyLive Plus (mobilna aplikacija) - Dozne BA-01, PFA1230R, PFA12C 	81.00	97.20
VNT01007		<p><u>TC-C34UV Spec: W/E/Y/M/S/4mm</u></p> <ul style="list-style-type: none"> - 4MP bulit WL kamera, - 4 mm F1.0 fiksni objektiv, - Vidni ugao 94.5°(H); 50.2°(V), - WL diode dometa 15m, - Integrisan mikrofon, - Slot za memorijsku karticu microSD/microSDHC/microSDXC do 512Gb, - Metalno kućište, - Dimenzije 239 x 90 x 90 mm, - Radna temperatura -40°C~+65°C, - IP67 sertifikovana, - Napajanje PoE, DC 12V ±25%, potrošnja do 9W, - WDR, BLC, HLC, AGC, 3D DNR, MD, Tripwire, Perimeter, Osoba/Vozilo klasifikacija, - WEB Browser, Easy7 VMS, EasyLive Plus (mobilna aplikacija) - Dozne PFA130, PFA135 	120.00	144.00

VNT01003		<p><u>TC-C34QN Spec: I5W/E/Y/2.8mm/V4.2</u></p> <ul style="list-style-type: none"> - 4MP bulit IC + WL kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 100.1°(H); 54.3°(V), - Smart IR diode dometa 50m, WL diode dometa 15m, - Integrisan mikrofon, - Metal + plastika kućište, - Dimenzije 164 x 73 x 73 mm, - Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje PoE, DC 12V ±25%, potrošnja do 7W, - WDR, BLC, HLC, AGC, 3D DNR, MD, Tripwire, Perimeter, - WEB Browser, Easy7 VMS, EasyLive Plus (mobilna aplikacija) - Dozne PFA134, PFA130 	81.00	97.20
Tiandy IPC 5MP				
VNT01006		<p><u>TC-C35XS Spec:</u> <u>I3W/E/Y/M/S/2.8mm/V5.0</u></p> <ul style="list-style-type: none"> - 5MP dom IC + WL Starlight kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 109°(H); 59°(V), - Smart IR diode dometa 30m, WL diode dometa 15m, - Integrisan mikrofon, - Slot za memorijsku karticu microSD/microSDHC/microSDXC do 512Gb, - Metalno kućište, - Dimenzije 117 x 117 x 96 mm, - Radna temperatura -40°C~+65°C, - IP67 sertifikovana, - Napajanje PoE, DC 12V ±25%, potrošnja do 5W, - WDR, BLC, HLC, AGC, 3D DNR, MD, Tripwire, Perimeter, - WEB Browser, Easy7 VMS, EasyLive Plus (mobilna aplikacija) - Dozne BA-01, PFA1230R, PFA12C 	110.00	132.00

VNT01005		<p><u>TC-C35WS Spec:</u> <u>I5W/E/Y/M/S/2.8mm/V5.0</u></p> <ul style="list-style-type: none"> - 5MP bulit IC + WL Starlight kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 109°(H); 59°(V), - Smart IR diode dometa 50m, WL diode dometa 15m, - Integrisan mikrofon, - Slot za memorijsku karticu microSD/microSDHC/microSDXC do 512Gb, - Metalno kućište, - Dimenzije 160 x 73 x 73 mm, - Radna temperatura -40°C~+65°C, - IP67 sertifikovana, - Napajanje PoE, DC 12V ±25%, potrošnja do 7,5W, - WDR, BLC, HLC, AGC, 3D DNR, MD, Tripwire, Perimeter, - WEB Browser, Easy7 VMS, EasyLive Plus (mobilna aplikacija) - Dozne PFA134, PFA130 	110.00	132.00
Tiandy snimači				
VNT02001		<p><u>TC-R3105 Spec: I/B/P4/L/S</u></p> <ul style="list-style-type: none"> - 5 kanalni NVR sa 4 PoE portova, Plug and play - Rezolucije snimanja 5 MP; 4 MP; 3 MP; 1080p; UXGA; 720p; VGA; 4CIF; DCIF; 2CIF; CIF; QCIF - Kapacitet dekodiranja 1-kanal 5 MP; 1-kanal 4 MP; 1-kanal 3MP; 2-kanala 1080p; 4-kanala 720p - Detekcija pokreta, Napredna inteligencija podrzana od kamera na aplikacijama - 1 HDMI izlaz, - 1 SATA HDD do 6TB, - PoE ukupne snage 45W, maksimalna snaga PoE porta 30W, maksimalna struja PoE porta 600mA, - 2 USB2.0 - Dimenzije 200 x 200 x 43 mm - Napajanje DC48V 1.35A - Radna temperatura -10°C~+55°C 	95.00	114.00

<p>VNT02002</p>		<p><u>TC-R3110 Spec:I/B/P8/L/S</u></p> <ul style="list-style-type: none"> - 10 kanalni NVR sa 8 PoE portova, Plug and play - Rezolucije snimanja 6 MP; 5 MP; 4 MP; 3 MP; 1080p; UXGA; 720p; VGA; 4CIF; DCIF; 2CIF; CIF; QCIF - Kapacitet dekodiranja 1-kanal 6 MP; 1-kanal 5 MP; 1-kanal 4 MP; 2-kanal 3MP; 3-kanala 1080p; 4-kanala 720p - Detekcija pokreta, Napredna inteligencija podrzana od kamera na aplikacijama - 1 HDMI izlaz, - 1 SATA HDD do 6TB, - PoE ukupne snage 70W, maksimalna snaga PoE porta 30W, maksimalna struja PoE porta 600mA, - 2 USB2.0 - Dimenzije 200 x 200 x 43 mm - Napajanje DC48V 1.875A - Radna temperatura -10°C ~ +55°C 	<p>150.00</p>	<p>180.00</p>
<p>VNT02003</p>		<p><u>TC-R3220 Spec:I/B/K/V3.1</u></p> <ul style="list-style-type: none"> - 20 kanalni NVR - Rezolucije snimanja 8 MP: 6 MP; 5 MP; 4 MP; 3 MP; 1080p; UXGA; 720p; VGA; 4CIF; DCIF; 2CIF; CIF; QCIF - Kapacitet dekodiranja: 2-kanalni 8 MP (30fps); 2-kanal 6 MP (30fps); 3-kanal 5 MP (30fps); 4-kanal 4 MP (30fps); 5-kanal 3MP (30fps); 8-kanala 1080p (30fps); 16-kanala 720p (30fps) - Detekcija pokreta, Face Detection, Napredna AI podrzana od kamera (Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing; Running; Parking; Heatmap; Loitering; Crowd Detection; Electric Bicycle Detection; People Counting; Link to Tracking; Smoke and Fire Detection; Environmental Temperature Measurement; Face Detection; Human Body Temperature Measurement; Smart Alarm; Human/Vehicle Classification) - 1 RJ45 10/100/1000 Mbps - 1 HDMI, 1 VGA izlaz, - 1 Audio ulaz, 1 Audio ulaz - Alarm I/O (4-ch, TTL inputs, 3mA, 	<p>235.00</p>	<p>282.00</p>

		<p>3.3VDC; 1-ch, relay output, 1A, 24VDC)</p> <ul style="list-style-type: none"> - 2 SATA HDD do 10TB, - 2 USB2.0 - Dimenzije 341 x 273 x 43 mm - Napajanje DC12V 3.33A - Radna temperatura -10°C~+55°C 		
Tiandy PoE switchevi				
MO070001		<p><u>TC-P3S06 Spec:F/0420/AT/55 switch 4 porta PoE 55W</u></p> <ul style="list-style-type: none"> - 4 X RJ45 10/100Mbps (PoE), 2 X RJ45 10/100Mbps (uplink) - PoE standard: IEEE802.3af (15.4W) IEEE802.3at (30W) - Switching Capacity 1,2 Gbps - Packet Forwarding Rate 0,8928 Mpps - Packet Buffer Size 448 Kbit - MAC Table Size 1K - PoE snaga: 55W - Podesavanje preko DIP prekidača: VLAN (mod izolacije PoE portova, Watchdog uključen), Default, Extend (PoE portovi do 10Mbps, dužina kabla do 220m, Watchdog uključen), - Radna temperatura -10 °C do +50 °C - Napajanje AC/DC adapter 52V, 1,25A - Dimenzije 200 × 118 × 44 mm 	55.00	66.00
MO070002		<p><u>TC-P3S010 Spec:H/0820/AT/90 switch 8 portova PoE 90W</u></p> <ul style="list-style-type: none"> - 8 X RJ45 10/100 Mbps (PoE), 2 X RJ45 10/100Mbps (uplink) - PoE standard: IEEE802.3af (15.4W) IEEE802.3at (30W) - Switching Capacity 5,6 Gbps - Packet Forwarding Rate 4,166 Mpps - Packet Buffer Size 448 Kbit - MAC Table Size 2K - PoE snaga: 90W - Podesavanje preko DIP prekidača: VLAN (mod izolacije PoE portova, Watchdog uključen), Default, Extend (PoE portovi do 10Mbps, dužina kabla do 220m, Watchdog uključen), - Radna temperatura -10 °C do +50 °C - Napajanje AC/DC adapter 52V, 1,92A - Dimenzije 200 × 118 × 44 mm 	65.00	78.00

MO70003		<p><u>TC-P3S010 Spec:G/0820/AT/110 switch 8 portova Gigabit PoE 110W</u></p> <ul style="list-style-type: none"> - 8 X RJ45 10/100/1000Mbps (PoE), 2 X RJ45 10/100/1000 Mbps (uplink) - PoE standard: IEEE802.3af (15.4W) IEEE802.3at (30W) - Switching Capacity 20 Gbps - Packet Forwarding Rate 14,88 Mpps - Packet Buffer Size 448 Kbit - MAC Table Size 2K - PoE snaga: 110W - Podesavanje preko DIP prekidaca: VLAN (mod izolacije PoE portova, Watchdog uključen), Default, Extend (PoE portovi do 10Mbps, dužina kabla do 220m, Watchdog uključen), - Radna temperatura -10 °C do +50 °C - Napajanje AC/DC adapter 52V, 2,3A - Dimenzije 220 × 161 × 44 mm 	75.00	90.00
MO070004		<p><u>TC-P3S019 Spec:H/1621/AT/180 switch 16 portova PoE 180W</u></p> <ul style="list-style-type: none"> - 16 X RJ45 10/100Mbps (PoE), 2 X RJ45 10/100/1000 Mbps (uplink), 1 X SFP 1000 Mbps - PoE standard: IEEE802.3af (15.4W) IEEE802.3at (30W) - Switching Capacity 99,2 Gbps - Packet Forwarding Rate 6,84 Mpps - Packet Buffer Size 3 Mbit - MAC Table Size 2K - PoE snaga: 180W - Podesavanje preko DIP prekidaca: VLAN (mod izolacije PoE portova, Watchdog uključen), Default, Extend (PoE portovi do 10Mbps, dužina kabla do 220m, Watchdog uključen), - Radna temperatura -10 °C do +50 °C - Napajanje AC/DC adapter 52V, 3,84A - Dimenzije 320 × 207 × 45 mm 	180.00	216.00